

### **KRP-C-3800SP Information**

Part Number KRP-C-3800SP

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 3.8K 600VAC/300VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KRP-C-3800SP Specifications**

Manufacturer Part Number  Manufacturer  Eaton  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  LOW-PEAK? KRP-C  Fuse Type  Cartridge  Current Rating  3.8K  Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Size / Divary 2, 350° L (146 OSmm x 95 25mm)	•	
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  LOW-PEAK? KRP-C  Fuse Type  Cartridge  Current Rating  3.8K  Voltage Rating - AC  600V  Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Circuit Protection  Electrical, Specialty Fuses  Cartridge  Cartridg	Manufacturer Part Number	KRP-C-3800SP
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series LOW-PEAK? KRP-C  Fuse Type Cartridge Current Rating 3.8K Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt)	Manufacturer	Eaton
Package Cylindrical, Blade Terminal (Bolt)  Series LOW-PEAK? KRP-C  Fuse Type Cartridge  Current Rating 3.8K  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Slow  Applications Electrical, Industrial  Features -  Class L  Approvals CE, CSA, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)	Category	Circuit Protection
Series LOW-PEAK? KRP-C Fuse Type Cartridge Current Rating 3.8K Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt)		Electrical, Specialty Fuses
Fuse Type Current Rating 3.8K  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Slow Applications Electrical, Industrial  Features - Class L Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cartridge 600V  AU 600V  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  CUL CUL COL COL COL COL COL COL COL COL COL CO	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating  3.8K  Voltage Rating - AC  600V  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  3.8K  C00V	Series	LOW-PEAK? KRP-C
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  600V  300V  Response Time  Clove  Slow  Clectrical, Industrial  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  CUL  Bolt Mount  CE, CSA, UL  CUL  CUL  CUL  CUL  CUL  CUL  CUL	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case 300V Electrical, Industrial - Ele	Current Rating	3.8K
Response Time Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Slow Slow CE, CSA, Industrial - CE, CSA, UL CE,	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class L  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)	Voltage Rating - DC	300V
Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt)	Response Time	Slow
Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt)	Applications	Electrical, Industrial
Approvals  CE, CSA, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt)	Class	L
Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt)	Breaking Capacity @ Rated Voltage	300kA AC, 100kA DC
	Mounting Type	Bolt Mount
Size / Dimension 5.750" Dia v. 3.750" I. (146.05mm v. 05.25mm)	Package / Case	Cylindrical, Blade Terminal (Bolt)
5.750 Dia x 5.750 L (140.0511111 x 75.2511111)	Size / Dimension	5.750" Dia x 3.750" L (146.05mm x 95.25mm)
Report errors?		Report errors?

### **KRP-C-3800SP Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KRP-C-3800SP Payment Methods**





















## **KRP-C-3800SP Shipping Methods**













If you have any question about KRP-C-3800SP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com