

KRP-C-5000SP Information

Part Number KRP-C-5000SP

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 5KA 600VAC/300VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KRP-C-5000SP Specifications

Manufacturer Part NumberKRP-C-5000SPManufacturerEatonCategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLOW-PEAK? KRP-CFuse TypeCartridgeCurrent Rating5kAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300K A C, 100K A DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension6.250" Dia x 3.750" L (158.75mm x 95.25mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLOW-PEAK? KRP-CFuse TypeCartridgeCurrent Rating5kAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Manufacturer Part Number	KRP-C-5000SP
Beaking Capacity @ Rated Voltage Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) LOW-PEAK? KRP-C Fuse Type Cartridge Current Rating SkA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Fuse Time Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - CE, CSA, UL Operating Temperature - CE, CSA, UL Operating Temperature - CE, CSA, UL Operating Temperature - CUINDRIAN DC Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesLOW-PEAK? KRP-CFuse TypeCartridgeCurrent Rating5kAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Category	Circuit Protection
SeriesLOW-PEAK? KRP-CFuse TypeCartridgeCurrent Rating5kAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension6.250" Dia x 3.750" L (158.75mm x 95.25mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 5kA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Canon Capacity (Start Start) Start Sta	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Size / Dimension Size / Dimension Size / Si	Series	LOW-PEAK? KRP-C
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Slow Slow Slow Slow Slow Slow Slow	Current Rating	5kA
Response Time Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Voltage Rating - DC	300V
Features - Class L Approvals CE, CSA, UL Operating Temperature - Seraking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Response Time	Slow
Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Class	L
Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Breaking Capacity @ Rated Voltage	300kA AC, 100kA DC
Size / Dimension 6.250" Dia x 3.750" L (158.75mm x 95.25mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
	Size / Dimension	6.250" Dia x 3.750" L (158.75mm x 95.25mm)
Report errors?		Report errors?

KRP-C-5000SP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KRP-C-5000SP Payment Methods



















KRP-C-5000SP Shipping Methods













If you have any question about KRP-C-5000SP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com