

KRP-CL-225 Information

Part Number KRP-CL-225

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 225A 600VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KRP-CL-225 Specifications

| Manufacturer Part NumberKRP-CL-225ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesHI-CAP? KRP-CLFuse TypeCartridgeCurrent Rating225AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.750" L (63.50mm x 95.25mm)Report errors? | | |
|--|-----------------------------------|---|
| Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series HI-CAP? KRP-CL Fuse Type Cartridge Current Rating 225A Voltage Rating - AC 600V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension | Manufacturer Part Number | KRP-CL-225 |
| PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesHI-CAP? KRP-CLFuse TypeCartridgeCurrent Rating225AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Manufacturer | Eaton |
| PackageCylindrical, Blade Terminal (Bolt)SeriesHI-CAP? KRP-CLFuse TypeCartridgeCurrent Rating225AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Category | Circuit Protection |
| SeriesHI-CAP? KRP-CLFuse TypeCartridgeCurrent Rating225AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.750" L (63.50mm x 95.25mm) | | Electrical, Specialty Fuses |
| Fuse TypeCartridgeCurrent Rating225AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Package | Cylindrical, Blade Terminal (Bolt) |
| Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 225A 600V - Clov L Approvals - Cless L Cless L Class L Class Clas | Series | HI-CAP? KRP-CL |
| Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600V - | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class Clow Class | Current Rating | 225A |
| Response Time Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Electrical, Industrial - Bleatrical, Industrial - Class Culss Cylindrical, Blade Terminal (Bolt) 2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Voltage Rating - AC | 600V |
| Applications Electrical, Industrial Features - Class L Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Voltage Rating - DC | - |
| Features - Class L Approvals - Coperating Temperature - Coperating Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Response Time | Slow |
| Class L Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension L Culture Culture Cylindrical, Blade Terminal (Bolt) | Applications | Electrical, Industrial |
| Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Class | L |
| Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Approvals | - |
| Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Operating Temperature | - |
| Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Breaking Capacity @ Rated Voltage | 200kA |
| Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm) | Mounting Type | Bolt Mount |
| | Package / Case | Cylindrical, Blade Terminal (Bolt) |
| Report errors? | Size / Dimension | 2.500" Dia x 3.750" L (63.50mm x 95.25mm) |
| | | Report errors? |

KRP-CL-225 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KRP-CL-225 Payment Methods



















KRP-CL-225 Shipping Methods













If you have any question about KRP-CL-225, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com