



### **KRPA-11AG-24 Information**



For Reference Only

Part Number KRPA-11AG-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KRPA-11AG-24 Specifications**

Manufacturer Part NumberKRPA-11AG-24ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKRPARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)20.4 VACTurn Off Voltage (Min)-Operate Time-Release Time-		
Category  Relays  Power Relays, Over 2 Amps  Package  - Series  KRPA  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  84mA  Coil Voltage  24VAC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Relays  Endest Series  Relays  Apower Relays, Over 2 Amps  Power Relays, Over 2 Amps  10  A  A  A  A  A  A  A  A  A  A  A  A  A	Manufacturer Part Number	KRPA-11AG-24
Package - Series KRPA Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 1240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time -	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KRPA Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 140VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time -	Category	Relays
SeriesKRPARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)20.4 VACTurn Off Voltage (Min)-Operate Time-		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 84mA  Coil Voltage 24VAC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 10A  Switching Voltage 240VAC - Max  Turn On Voltage (Max) 20.4 VAC  Turn Off Voltage (Min) -  Operate Time -	Package	-
Coil Type Non Latching  Coil Current 84mA  Coil Voltage 24VAC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 10A  Switching Voltage 240VAC - Max  Turn On Voltage (Max) 20.4 VAC  Turn Off Voltage (Min) -  Operate Time -	Series	KRPA
Coil Current 84mA  Coil Voltage 24VAC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 10A  Switching Voltage 240VAC - Max  Turn On Voltage (Max) 20.4 VAC  Turn Off Voltage (Min) -  Operate Time -	Relay Type	General Purpose
Coil Voltage 24VAC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 10A  Switching Voltage 240VAC - Max  Turn On Voltage (Max) 20.4 VAC  Turn Off Voltage (Min) -  Operate Time -	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  7urn Off Voltage (Min)  Operate Time  DPDT (2 Form C)  10A  240VAC - Max	Coil Current	84mA
Contact Rating (Current)  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  7urn Off Voltage (Min)  Operate Time	Coil Voltage	24VAC
Switching Voltage 240VAC - Max  Turn On Voltage (Max) 20.4 VAC  Turn Off Voltage (Min) -  Operate Time -	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 20.4 VAC  Turn Off Voltage (Min) -  Operate Time -	Contact Rating (Current)	10A
Turn Off Voltage (Min) - Operate Time -	Switching Voltage	240VAC - Max
Operate Time -	Turn On Voltage (Max)	20.4 VAC
	Turn Off Voltage (Min)	-
Release Time -	Operate Time	-
	Release Time	-
Features Insulation - Class B	Features	Insulation - Class B
Mounting Type Socketable	Mounting Type	Socketable
Termination Style Plug In, 8 Pin (Octal)	Termination Style	Plug In, 8 Pin (Octal)
Report errors?		Report errors?

#### **KRPA-11AG-24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KRPA-11AG-24 Payment Methods**



















## **KRPA-11AG-24 Shipping Methods**













If you have any question about KRPA-11AG-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com