

### **KRPA-14AG-120 Information**



For Reference Only

Part Number KRPA-14AG-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 10A 120V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **KRPA-14AG-120 Specifications**

Manufacturer Part NumberKRPA-14AG-120ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKRPARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17.5mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         KRPA           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         17.5mA           Coil Voltage         120VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         240VAC - Max           Turn On Voltage (Max)         102 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         Insulation - Class B           Mounting Type         Socketable           Termination Style         Plug In, 11 Pin (Octal)	Manufacturer Part Number	KRPA-14AG-120
Package         -           Series         KRPA           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         17.5mA           Coil Voltage         120VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         240VAC - Max           Turn On Voltage (Max)         102 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         Insulation - Class B           Mounting Type         Socketable           Termination Style         Plug In, 11 Pin (Octal)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         KRPA           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         17.5mA           Coil Voltage         120VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         240VAC - Max           Turn On Voltage (Max)         102 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         Insulation - Class B           Mounting Type         Socketable           Termination Style         Plug In, 11 Pin (Octal)	Category	Relays
SeriesKRPARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17.5mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 17.5mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features Insulation - Class B Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Package	-
Coil TypeNon LatchingCoil Current17.5mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Series	KRPA
Coil Current Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time Release Time - Features Insulation - Class B Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time Insulation - Class B Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C)  Contact Rating (Current) 10A  Switching Voltage 240VAC - Max  Turn On Voltage (Max) 102 VAC  Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Coil Current	17.5mA
Contact Rating (Current)  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  102 VAC  Turn Off Voltage (Min)  Operate Time  - Release Time  - Features  Insulation - Class B  Mounting Type  Socketable  Termination Style  Plug In, 11 Pin (Octal)	Coil Voltage	120VAC
Switching Voltage 240VAC - Max  Turn On Voltage (Max) 102 VAC  Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max)  102 VAC  Turn Off Voltage (Min)  Operate Time  Release Time  -  Features  Insulation - Class B  Mounting Type  Socketable  Termination Style  Plug In, 11 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  Release Time  Features  Insulation - Class B  Mounting Type  Socketable  Termination Style  Plug In, 11 Pin (Octal)	Switching Voltage	240VAC - Max
Operate Time	Turn On Voltage (Max)	102 VAC
Release Time - Features Insulation - Class B Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn Off Voltage (Min)	-
Features Insulation - Class B  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Operate Time	-
Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Release Time	-
Termination Style Plug In, 11 Pin (Octal)	Features	Insulation - Class B
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 11 Pin (Octal)
		Report errors?

#### **KRPA-14AG-120 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **KRPA-14AG-120 Payment Methods**



















### **KRPA-14AG-120 Shipping Methods**













If you have any question about KRPA-14AG-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com