

KRPA-14AN-24 Information



For Reference Only

Part Number KRPA-14AN-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KRPA-14AN-24 Specifications

Manufacturer Part Number KRPA-14AN-24 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series KRPA Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKRPARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage24VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)20.4 VACTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class B, Incandescent IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer Part Number	KRPA-14AN-24
Package - Series KRPA Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KRPA Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Category	Relays
SeriesKRPARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage24VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)20.4 VACTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class B, Incandescent IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Package	-
Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Series	KRPA
Coil Current Coil Voltage 24VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 24VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Current	84mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) Operate Time - Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Voltage	24VAC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) Operate Time Release Time - Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time Release Time Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Switching Voltage	240VAC - Max
Operate Time - Release Time - Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn On Voltage (Max)	20.4 VAC
Release Time - Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn Off Voltage (Min)	-
Features Insulation - Class B, Incandescent Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Operate Time	-
Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Release Time	-
Termination Style Plug In, 11 Pin (Octal)	Features	Insulation - Class B, Incandescent Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 11 Pin (Octal)
		Report errors?

KRPA-14AN-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KRPA-14AN-24 Payment Methods



















KRPA-14AN-24 Shipping Methods













If you have any question about KRPA-14AN-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com