

KRS10F-24 Information

Part Number KRS10F-24

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - Board Mount

AC DC Converters

Description POWER SUPPLY SW UNIV-INP 24V 10W

Package 5-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KRS10F-24 Specifications

Manufacturer Part Number KRS10F-24 Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - Board Mount AC DC Converters Package 5-DIP Module Series KRS10F Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Applications ITE (Commercial) Peatures OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm) Report errors?		
Category Power Supplies - Board Mount AC DC Converters Package 5-DIP Module Series KRS10F Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Manufacturer Part Number	KRS10F-24
Package 5-DIP Module Series KRS10F Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package 5-DIP Module Series KRS10F Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Category	Power Supplies - Board Mount
Series KRS10F Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Package	5-DIP Module
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Series	KRS10F
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Туре	Open Frame
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Features OCP, OVP Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension - Voltage - Output 2 - Current - Output (Max)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Features OCP, OVP Operating Temperature Efficiency 82% Mounting Type Through Hole Package / Case Size / Dimension - Current - Output (Max) 420mA - 10W Features OCP, OVP OCP, OVP (With Derating) Efficiency 82% Through Hole Size / Dimension - 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension - Commercial (With Derating) - Comme	Voltage - Output 2	-
Current - Output (Max) 420mA Power (Watts) 10W Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 10W ITE (Commercial) OCP, OVP (With Derating) Features 10°C ~ 70°C (With Derating) 82% Through Hole 10°C ~ 70°C (With Derating)	Voltage - Output 4	-
Applications ITE (Commercial) Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Current - Output (Max)	420mA
Features OCP, OVP Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Power (Watts)	10W
Operating Temperature 10°C ~ 70°C (With Derating) Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Applications	ITE (Commercial)
Efficiency 82% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Features	OCP, OVP
Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Operating Temperature	10°C ~ 70°C (With Derating)
Package / Case 5-DIP Module Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Efficiency	82%
Size / Dimension 2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)	Mounting Type	Through Hole
	Package / Case	5-DIP Module
Report errors?	Size / Dimension	2.56" L x 1.26" W x 0.65" H (65.0mm x 32.0mm x 16.5mm)
		Report errors?

KRS10F-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KRS10F-24 Payment Methods



















KRS10F-24 Shipping Methods













If you have any question about KRS10F-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com