

#### **KRS25F-05 Information**

Part Number KRS25F-05

Manufacturer Volgen America/Kaga Electronics USA

**Category** Power Supplies - Board Mount

AC DC Converters

**Description** POWER SUPPLY SW UNIV-IN 5V 25W

Package 5-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KRS25F-05 Specifications**

Manufacturer Part Number         KRS25F-05           Manufacturer         Volgen America/Kaga Electronics USA           Category         Power Supplies - Board Mount           AC DC Converters           Package         5-DIP Module           Series         KRS25F           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         5A           Power (Watts)         25W           Applications         ITE (Commercial)           Features         OCP, OVP           Operating Temperature         0°C ~ 70°C (With Derating)           Efficiency         74%           Mounting Type         Through Hole           Package / Case         5-DIP Module           Size / Dimension         3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)		
Category         Power Supplies - Board Mount           AC DC Converters           Package         5-DIP Module           Series         KRS25F           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         5A           Power (Watts)         25W           Applications         ITE (Commercial)           Features         OCP, OVP           Operating Temperature         0°C ~ 70°C (With Derating)           Efficiency         74%           Mounting Type         Through Hole           Package / Case         5-DIP Module           Size / Dimension         3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Manufacturer Part Number	KRS25F-05
Package         5-DIP Module           Series         KRS25F           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         5A           Power (Watts)         25W           Applications         ITE (Commercial)           Features         OCP, OVP           Operating Temperature         0°C ~ 70°C (With Derating)           Efficiency         74%           Mounting Type         Through Hole           Package / Case         5-DIP Module           Size / Dimension         3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package         5-DIP Module           Series         KRS25F           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         5A           Power (Watts)         25W           Applications         ITE (Commercial)           Features         OCP, OVP           Operating Temperature         0°C ~ 70°C (With Derating)           Efficiency         74%           Mounting Type         Through Hole           Package / Case         5-DIP Module           Size / Dimension         3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Category	Power Supplies - Board Mount
Series         KRS25F           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         5A           Power (Watts)         25W           Applications         ITE (Commercial)           Features         OCP, OVP           Operating Temperature         0°C ~ 70°C (With Derating)           Efficiency         74%           Mounting Type         Through Hole           Package / Case         5-DIP Module           Size / Dimension         3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         5A           Power (Watts)         25W           Applications         ITE (Commercial)           Features         OCP, OVP           Operating Temperature         0°C ~ 70°C (With Derating)           Efficiency         74%           Mounting Type         Through Hole           Package / Case         5-DIP Module           Size / Dimension         3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Package	5-DIP Module
Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         5A           Power (Watts)         25W           Applications         ITE (Commercial)           Features         OCP, OVP           Operating Temperature         0°C ~ 70°C (With Derating)           Efficiency         74%           Mounting Type         Through Hole           Package / Case         5-DIP Module           Size / Dimension         3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Series	KRS25F
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         5A           Power (Watts)         25W           Applications         ITE (Commercial)           Features         OCP, OVP           Operating Temperature         0°C ~ 70°C (With Derating)           Efficiency         74%           Mounting Type         Through Hole           Package / Case         5-DIP Module           Size / Dimension         3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Туре	Open Frame
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  Features  OCP, OVP  Operating Temperature  Efficiency  Mounting Type  Through Hole  Package / Case  Size / Dimension  5V  Siva - Applications  5V  Current - Output (Max)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  Features  OCP, OVP  Operating Temperature  O°C ~ 70°C (With Derating)  Efficiency  Mounting Type  Through Hole  Package / Case  Size / Dimension	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  Features  OCP, OVP  Operating Temperature  O°C ~ 70°C (With Derating)  Efficiency  Mounting Type  Through Hole  Package / Case  Size / Dimension  -  Size / Dimension  Six - Output (Max)  -  Current - Output (Max)  5A  Current - Output (Max)  5A  Commercial)  Commercial)  Six - 70°C (With Derating)  The (With Derating)  Through Hole  Size / Dimension  3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Voltage - Output 1	5V
Voltage - Output 4  Current - Output (Max)  5A  Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OVP  Operating Temperature  0°C ~ 70°C (With Derating)  Efficiency  74%  Mounting Type  Through Hole  Package / Case  5-DIP Module  Size / Dimension	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  25W  Applications  ITE (Commercial)  Features  OCP, OVP  Operating Temperature  0°C ~ 70°C (With Derating)  Efficiency  74%  Mounting Type  Through Hole  Package / Case  5-DIP Module  Size / Dimension  5A  25W  Commercial)  OCP, OVP  OVP  OPP  Through Hole  Through Hole  Size / Dimension  3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OVP  Operating Temperature  0°C ~ 70°C (With Derating)  Efficiency  74%  Mounting Type  Through Hole  Package / Case  5-DIP Module  Size / Dimension  25W  OCP, OVP  OCP, OVP  OPP  OPP  OPP  OPP  OPP  OPP  OPP	Voltage - Output 4	-
Applications ITE (Commercial)  Features OCP, OVP  Operating Temperature 0°C ~ 70°C (With Derating)  Efficiency 74%  Mounting Type Through Hole  Package / Case 5-DIP Module  Size / Dimension 3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Current - Output (Max)	5A
Features OCP, OVP Operating Temperature 0°C ~ 70°C (With Derating)  Efficiency 74%  Mounting Type Through Hole  Package / Case 5-DIP Module  Size / Dimension 3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Power (Watts)	25W
Operating Temperature 0°C ~ 70°C (With Derating)  Efficiency 74%  Mounting Type Through Hole  Package / Case 5-DIP Module  Size / Dimension 3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Applications	ITE (Commercial)
Efficiency 74%  Mounting Type Through Hole  Package / Case 5-DIP Module  Size / Dimension 3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Features	OCP, OVP
Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Package / Case         5-DIP Module           Size / Dimension         3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Efficiency	74%
Size / Dimension 3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)	Mounting Type	Through Hole
	Package / Case	5-DIP Module
Report errors?	Size / Dimension	3.35" L x 1.61" W x 0.91" H (85.0mm x 41.0mm x 23.0mm)
		Report errors?

#### **KRS25F-05 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KRS25F-05 Payment Methods**

































If you have any question about KRS25F-05, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com