

Heisener.com

### **KS55 Information**

Part Number KS55

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** SWITCHING POWER SUPPLIES

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









<b>KS55</b>	Snec	rifics	tions
<b>V222</b>	Spec	HIIC	เนบแร

Manufacturer Part Number         KS55           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         KS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1A           Power (Watts)         5W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         -           Operating Temperature         10°C ~ 70°C (With Derating)           Features         DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)           Report errors?				
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         KS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1A           Power (Watts)         5W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         -           Operating Temperature         10°C ~ 70°C (With Derating)           Features         DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Manufacturer Part Number	KS55		
Package         -           Series         KS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1A           Power (Watts)         5W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         -           Operating Temperature         10°C ~ 70°C (With Derating)           Features         DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Manufacturer	TDK-Lambda Americas Inc.		
Package         -           Series         KS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1A           Power (Watts)         5W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         -           Operating Temperature         10°C ~ 70°C (With Derating)           Features         DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series         KS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1A           Power (Watts)         5W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         -           Operating Temperature         10°C ~ 70°C (With Derating)           Features         DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)		AC DC Converters		
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1A           Power (Watts)         5W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         -           Operating Temperature         10°C ~ 70°C (With Derating)           Features         DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Package	-		
Number of Outputs       1         Voltage - Input       85 ~ 132 VAC         Voltage - Output 1       5V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       1A         Power (Watts)       5W         Applications       ITE (Commercial)         Voltage - Isolation       2kV (2000V)         Efficiency       -         Operating Temperature       10°C ~ 70°C (With Derating)         Features       DC Input Capable         Mounting Type       Chassis Mount         Size / Dimension       1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Series	KS		
Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1A           Power (Watts)         5W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         -           Operating Temperature         10°C ~ 70°C (With Derating)           Features         DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Type	Enclosed		
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Efficiency  Operating Temperature  DC Input Capable  Mounting Type  Size / Dimension  5V  - Current - Output (Max)  1A  - Current - Output (Max	Number of Outputs	1		
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  2kV (2000V)  Efficiency  Operating Temperature  10°C ~ 70°C (With Derating)  Features  Mounting Type  Chassis Mount  Size / Dimension  - Current - Output (Max)  1A  - Current - Output (Max)  1A  SW  5W  Commercial)  6W  Comm	Voltage - Input	85 ~ 132 VAC		
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  2kV (2000V)  Efficiency  Operating Temperature  10°C ~ 70°C (With Derating)  Features  Mounting Type  Chassis Mount  Size / Dimension  - Output (Max)	Voltage - Output 1	5V		
Voltage - Output 4  Current - Output (Max)  1A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  2kV (2000V)  Efficiency  - Operating Temperature  10°C ~ 70°C (With Derating)  Features  DC Input Capable  Mounting Type  Chassis Mount  Size / Dimension  1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Voltage - Output 2	-		
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  2kV (2000V)  Efficiency  - Operating Temperature  10°C ~ 70°C (With Derating)  Features  DC Input Capable  Mounting Type  Chassis Mount  Size / Dimension  1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Voltage - Output 3	-		
Power (Watts) 5W  Applications ITE (Commercial)  Voltage - Isolation 2kV (2000V)  Efficiency - Operating Temperature 10°C ~ 70°C (With Derating)  Features DC Input Capable  Mounting Type Chassis Mount  Size / Dimension 1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Voltage - Output 4	-		
Applications ITE (Commercial)  Voltage - Isolation 2kV (2000V)  Efficiency -  Operating Temperature 10°C ~ 70°C (With Derating)  Features DC Input Capable  Mounting Type Chassis Mount  Size / Dimension 1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Current - Output (Max)	1A		
Voltage - Isolation 2kV (2000V)  Efficiency - Operating Temperature 10°C ~ 70°C (With Derating)  Features DC Input Capable  Mounting Type Chassis Mount  Size / Dimension 1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Power (Watts)	5W		
Efficiency - Operating Temperature 10°C ~ 70°C (With Derating) Features DC Input Capable Mounting Type Chassis Mount Size / Dimension 1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Applications	ITE (Commercial)		
Operating Temperature10°C ~ 70°C (With Derating)FeaturesDC Input CapableMounting TypeChassis MountSize / Dimension1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Voltage - Isolation	2kV (2000V)		
Features DC Input Capable  Mounting Type Chassis Mount  Size / Dimension 1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Efficiency	-		
Mounting Type Chassis Mount Size / Dimension 1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Operating Temperature	10°C ~ 70°C (With Derating)		
Size / Dimension 1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)	Features	DC Input Capable		
*	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	1.89" L x 1.69" W x 0.77" H (48.0mm x 43.0mm x 19.5mm)		
		Report errors		

### **KS55 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **KS55 Payment Methods**



















## **KS55 Shipping Methods**













If you have any question about KS55, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com