



KSA0M412 Information



For Reference Only

Part Number KSA0M412
Manufacturer C&K
Category Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 32V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KSA0M412 Specifications

| Manufacturer Part Number KSA0M412 Manufacturer C&K Category Switches Package - Series KSA Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - Report errors? | | |
|--|-----------------------------------|-------------------------------|
| Category Package Series KSA Circuit SPST-NO Switch Function Contact Rating @ Voltage Actuator Type Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Termination Style Outline Mounting Buther Actuator Mounting Type Actuator Orientation Top Actuated PC Pin Outline 6.20mm x 6.20mm Illumination Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection Features - KSA KSA Circuit SPST-NO SPST-NO Onf-Mom Actuator Actuator Actuator Actuator Jupe Actuated Tronph Hole 4.70mm Actuated Top Actuated Top Actuated Top Actuated PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features | Manufacturer Part Number | KSA0M412 |
| Package - Series KSA Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - ACUACO SPST-NO SP | Manufacturer | C&K |
| Package - Series KSA Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - Office Actuated - Operating Force Indeed IP67 - Dust Tight, Waterproof Features - Office Actuated Indeed Indeed IP67 - Dust Tight, Waterproof IP67 - Dust Tight | Category | Switches |
| SeriesKSACircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical4.70mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures- | | Tactile Switches |
| CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical4.70mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures- | Package | - |
| Switch Function Contact Rating @ Voltage Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features Outline Outline One Substitute | Series | KSA |
| Contact Rating @ Voltage Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated PC Pin Outline 6.20mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 32VDC Standard 1.009 Hole 4.70mm Actuator Ciph Hole 4.70mm Actuator Ciph Hole 4.70mm Actuator Length, Right Angle - Operating Force 300gf IP67 - Dust Tight, Waterproof Features | Circuit | SPST-NO |
| Actuator Type Mounting Type Through Hole Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Standard Through Hole A.70mm A | Switch Function | Off-Mom |
| Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style PC Pin Outline G.20mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Through Hole 4.70mm Finded Frough Hole 4.70mm Annual Hole 4.70mm Fore Actuated Frough Hole Fore Actuator Description Fore Actuated Frough Hole 4.70mm Fore Actuated Frough Hole Actuator Height off PCB, Vertical Actuat | Contact Rating @ Voltage | 0.05A @ 32VDC |
| Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features 4.70mm 4.70mm 4.70mm 4.70mm 4.70mm 4.70mm 5.70m 6.20mm x 6.20mm 7.70m 7. | Actuator Type | Standard |
| Actuator Length, Right Angle Actuator Orientation Top Actuated PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features | Mounting Type | Through Hole |
| Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - | Actuator Height off PCB, Vertical | 4.70mm |
| Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - | Actuator Length, Right Angle | - |
| Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - | Actuator Orientation | Top Actuated |
| IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures- | Termination Style | PC Pin |
| Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features - Illumination Type, Color - 300gf IP67 - Dust Tight, Waterproof - | Outline | 6.20mm x 6.20mm |
| Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - | Illumination | Non-Illuminated |
| Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - | Illumination Type, Color | - |
| Ingress Protection IP67 - Dust Tight, Waterproof Features - | Illumination Voltage (Nominal) | - |
| Features - | Operating Force | 300gf |
| | Ingress Protection | IP67 - Dust Tight, Waterproof |
| Report errors? | Features | - |
| | | Report errors? |

KSA0M412 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KSA0M412 Payment Methods





















KSA0M412 Shipping Methods













If you have any question about KSA0M412, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com