



KSA0M412LFT Information



For Reference Only

Part Number KSA0M412LFT

Manufacturer C&K **Category** Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 32V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KSA0M412LFT Specifications

Manufacturer Part Number KSA0M412LFT Manufacturer C&K Category Switches Package - Series KSA Circuit SPST-NO Switch Function Off-Mom Conact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features -		
CategorySwitchesPackage-SeriesKSACircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical4.70mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Manufacturer Part Number	KSA0M412LFT
Package - Series KSA Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - SPST-NO	Manufacturer	C&K
Package-SeriesKSACircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical4.70mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Category	Switches
SeriesKSACircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical4.70mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical4.70mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Series	KSA
Contact Rating @ Voltage Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline 6.20mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 32VDC Standard 0.005A @ 32VDC 0.005A	Circuit	SPST-NO
Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features - Standard Through Hole 4.70mm Actuator Orientation Commander Features Standard Ander Standard Ande	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline Blumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Through Hole 4.70mm Farmination Frough Hole 4.70mm Actuator Orientation Frough Hole 4.70mm Actuator One 4.70mm Frough Hole 4.70mm Actuator Length, Right Angle - Non-Illuminated - 100 - 101 - 102 - 103 - 104 - 105 - 106 - 107 - 108 - 108 - 109 - 109 - 109 - 100 - 1	Contact Rating @ Voltage	0.05A @ 32VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection Features 4.70mm 4.70mm 4.70mm 4.70mm 4.70mm 5.70m 5.70m 6.20mm 6	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Mounting Type	Through Hole
Actuator Orientation Top Actuated Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Height off PCB, Vertical	4.70mm
Termination Style PC Pin Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Length, Right Angle	-
Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Termination Style	PC Pin
Illumination Type, Color Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Outline	6.20mm x 6.20mm
Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Illumination	Non-Illuminated
Operating Force300gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Illumination Type, Color	-
Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	300gf
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	-
		Report errors?

KSA0M412LFT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KSA0M412LFT Payment Methods





















KSA0M412LFT Shipping Methods













If you have any question about KSA0M412LFT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com