

KSC321J Information



For Reference Only

Part Number KSC321J Manufacturer C&K Category Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 32V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KSC321J Specifications

Manufacturer Part Number KSC321J Manufacturer C&K Category Switches Package - Series KSC Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.50mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection IP67 - Dust Tight, Waterproof Features - Report errors?		
Category Package Series KSC Circuit SPST-NO Switch Function Contact Rating @ Voltage Actuator Type Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Termination Style Outline 6.20mm x 6.20mm Illumination Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) Operating Force 200gf Ingress Protection Features - KSC KSC SPST-NO Spathage - Onto Actuated 1. Top Actuated 2. Outline 6. 20mm x 6.20mm 1. Illuminated 1. Illuminated 1. Illumination Type, Color 1. Illumination Type, Color 1. Illumination Voltage (Nominal) 1. Operating Force 2. 200gf Ingress Protection IP67 - Dust Tight, Waterproof Features	Manufacturer Part Number	KSC321J
Package - Series KSC Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.50mm Actuator Length, Right Angle - Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection IP67 - Dust Tight, Waterproof Features - Offense SPST-NO SPS	Manufacturer	C&K
Package-SeriesKSCCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical3.50mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force200gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Category	Switches
Series KSC Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.50mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Type, Color - Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection IP67 - Dust Tight, Waterproof Features		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical3.50mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force200gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Package	-
Switch Function Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Outline 6.20mm x 6.20mm Illumination Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features Outlone One Actuated Outline Operating Force Operating Force Operating Force Operating Force One Actuator Orientation One Actuated Outline Operating Force Operating Oper	Series	KSC
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount 3.50mm Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 32VDC Standard 0.05A @ 32VDC Standard 0.06A @ 32VDC Standard 0.010 Surface Mount 3.50mm Actuator Departing Force J Lead - 200gf IP67 - Dust Tight, Waterproof Features	Circuit	SPST-NO
Actuator Type Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline 6.20mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Standard Surface Mount 3.50mm Features Surface Mount 3.50mm Fount Actuator Orientation Actuator Orientation Fon Actuated Fon Actuator Mount Fon Actuated Fon Actuator Mount	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount 3.50mm Non-Illumination Top Actuated	Contact Rating @ Voltage	0.05A @ 32VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features 3.50mm - Top Actuated - Top Actuated - Top Actuated - Top Actuated Top Actuated	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features - Top Actuated Top Actuated Top Actuated 200mm x 6.20mm Non-Illuminated - 100 -	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color	Actuator Height off PCB, Vertical	3.50mm
Termination Style Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force 200gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Length, Right Angle	-
Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force200gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Termination Style	J Lead
Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Outline	6.20mm x 6.20mm
Illumination Voltage (Nominal) Operating Force 200gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination	Non-Illuminated
Operating Force 200gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination Type, Color	-
Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	200gf
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	-
		Report errors?

KSC321J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KSC321J Payment Methods





















KSC321J Shipping Methods













If you have any question about KSC321J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com