



KSC423J 70SH LFG Information



For Reference Only

Part Number KSC423J 70SH LFG

Manufacturer C&K **Category** Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.01A 32V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KSC423J 70SH LFG Specifications

Manufacturer Part Number KSC423J 70SH LFG Manufacturer C&K Category Switches Package - Series KSC Circuit SPST-NO Switch Function Off-Mom Conact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 5.20mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection IP67 - Dust Tight, Waterproof Features -		
CategorySwitchesPackage-SeriesKSCCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical5.20mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Manufacturer Part Number	KSC423J 70SH LFG
Package - Series KSC Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 5.20mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection IP67 - Dust Tight, Waterproof Features - SPST-NO	Manufacturer	C&K
Package-SeriesKSCCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical5.20mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Category	Switches
Series KSC Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 5.20mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection IP67 - Dust Tight, Waterproof Features -		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical5.20mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 5.20mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Series	KSC
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.01A @ 32VDC Standard Stan	Circuit	SPST-NO
Actuator Type Surface Mount Actuator Height off PCB, Vertical 5.20mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection IP67 - Dust Tight, Waterproof Features - Surface Mount Surface Mount Surface Mount 5.20mm Top Actuated - Non-Illuminated 1 Lead 6.20mm x 6.20mm 1 Lead 6.20mm x 6.20mm 1 Lead 1 Lea	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount Surface Mount 5.20mm Non-Illumination Top Actuated Features Actuator Orientation Top Actuated Features Non-Illuminated I Lead 6.20mm x 6.20mm Illuminated Features I Lead Features I Lead I Le	Contact Rating @ Voltage	0.01A @ 32VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle - Common Top Actuated Termination Style Outline Outline 10	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features - Top Actuated Top Actuated Top Actuated Top Actuated 1 Lead 6.20mm x 6.20mm Non-Illuminated - 1 Features	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style J Lead Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Height off PCB, Vertical	5.20mm
Termination Style Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 160gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Length, Right Angle	-
Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Termination Style	J Lead
Illumination Type, Color Illumination Voltage (Nominal) Operating Force 160gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Outline	6.20mm x 6.20mm
Illumination Voltage (Nominal)-Operating Force160gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Illumination	Non-Illuminated
Operating Force160gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Illumination Type, Color	-
Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	160gf
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	-
		Report errors?

KSC423J 70SH LFG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KSC423J 70SH LFG Payment Methods



















KSC423J 70SH LFG Shipping Methods













If you have any question about KSC423J 70SH LFG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com