



KSC442G 70SH LFS Information



For Reference Only

Part Number KSC442G 70SH LFS

Manufacturer C&K

Category Switches
Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 32V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KSC442G 70SH LFS Specifications

Manufacturer Part Number Manufacturer C&K Category Switches Tactile Switches Package - Series KSC Circuit SPST-NO Switch Function Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline Gull Wing Outline 6.20mm x 6.20mm Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force 400gf Ingress Protection Features - Report errors?		
CategorySwitchesPackage-SeriesKSCCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical5.20mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force400gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Manufacturer Part Number	KSC442G 70SH LFS
Package - Series KSC Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 5.20mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Manufacturer	C&K
Package	Category	Switches
SeriesKSCCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical5.20mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force400gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-		Tactile Switches
Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 5.20mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Won-Illuminated Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 5.20mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Series	KSC
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline G.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 32VDC Standard Standard Standard Standard Standard Standard Surface Mount Surface M	Circuit	SPST-NO
Actuator Type Surface Mount Actuator Height off PCB, Vertical 5.20mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Gull Wing Outline 6.20mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount Surface Mount Surface Mount Surface Mount 5.20mm Non-Illumination Top Actuated Gull Wing 6.20mm x 6.20mm Non-Illuminated - Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 400gf Ip67 - Dust Tight, Waterproof Features	Contact Rating @ Voltage	0.05A @ 32VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 400gf Ingress Protection Features 5.20mm - Color Top Actuated Foundation Top Actuated Foundation Foundatio	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Gull Wing Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Height off PCB, Vertical	5.20mm
Termination Style Outline 6.20mm x 6.20mm Illumination Non-Illuminated - Illumination Type, Color Illumination Voltage (Nominal) Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Length, Right Angle	-
Outline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force400gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force400gfIngress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Termination Style	Gull Wing
Illumination Type, Color Illumination Voltage (Nominal) Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Outline	6.20mm x 6.20mm
Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination	Non-Illuminated
Operating Force 400gf Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination Type, Color	-
Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	400gf
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	-
		Report errors?

KSC442G 70SH LFS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KSC442G 70SH LFS Payment Methods



















KSC442G 70SH LFS Shipping Methods













If you have any question about KSC442G 70SH LFS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com