



KSL0M330 Information



For Reference Only

Part Number KSL0M330

Manufacturer C&K

Category Switches
Tactile Switches

Description SWITCH TACTILE SPST-NO 0.01A 50V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KSL0M330 Specifications

Manufacturer Part Number KSL0M330 Manufacturer C&K Category Switches Package - Series KSL Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 50VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 9.90mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection 1P40 Features - Report errors?		
Category Switches Package - Series KSL Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 50VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 9.90mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP40 Features -	Manufacturer Part Number	KSL0M330
Package - Series KSL Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 50VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 9.90mm Actuator Length, Right Angle - Top Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Type, Color - Illumination Type, Color 110mm in	Manufacturer	C&K
Package - Series KSL Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 50VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 9.90mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP40 Features -	Category	Switches
SeriesKSLCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 50VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical9.90mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline7.40mm x 7.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP40Features-		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 50VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical9.90mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline7.40mm x 7.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP40Features-	Package	-
Switch FunctionOff-MomContact Rating @ Voltage0.01A @ 50VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical9.90mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline7.40mm x 7.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP40Features-	Series	KSL
Contact Rating @ Voltage0.01A @ 50VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical9.90mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline7.40mm x 7.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP40Features-	Circuit	SPST-NO
Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 9.90mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP40 Features -	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style PC Pin Outline Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Through Hole 9.90mm Through Hole 9.90mm Top Actuated 1. Top Act	Contact Rating @ Voltage	0.01A @ 50VDC
Actuator Height off PCB, Vertical 9.90mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP40 Features -	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated PC Pin Outline 7.40mm x 7.40mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Mounting Type	Through Hole
Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 130gf Ingress Protection IP40 Features	Actuator Height off PCB, Vertical	9.90mm
Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP40 Features -	Actuator Length, Right Angle	-
Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP40 Features	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP40Features-	Termination Style	PC Pin
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP40Features-	Outline	7.40mm x 7.40mm
Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP40 Features -	Illumination	Non-Illuminated
Operating Force 130gf Ingress Protection IP40 Features -	Illumination Type, Color	-
Ingress Protection IP40 Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	130gf
	Ingress Protection	IP40
Report errors?	Features	-
		Report errors?

KSL0M330 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KSL0M330 Payment Methods



















KSL0M330 Shipping Methods













If you have any question about KSL0M330, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com