



KSL0V331 LFTR Information



For Reference Only

Part Number KSL0V331 LFTR

Manufacturer C&K **Category** Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.01A 32V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KSL0V331 LFTR Specifications

Manufacturer Part Number KSLOV331 LFTR Manufacturer C&K Category Switches Package - Series KSL Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Through Hole, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle 11.10mm Actuator Orientation Side Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP60 - Dust Tight Features - Report errors?		
CategorySwitchesPackage-SeriesKSLCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 32VDCActuator TypeStandardMounting TypeThrough Hole, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle11.10mmActuator OrientationSide ActuatedTermination StylePC PinOutline7.40mm x 7.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP60 - Dust TightFeatures-	Manufacturer Part Number	KSL0V331 LFTR
Package - Series KSL Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0,01A @ 32VDC Actuator Type Standard Mounting Type Through Hole, Right Angle - 1.10mm Actuator Height off PCB, Vertical - 1.10mm Actuator Length, Right Angle 11.10mm Actuator Orientation Side Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP60 - Dust Tight Features - 1.50cm	Manufacturer	C&K
Package - Series KSL Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Through Hole, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle 11.10mm Actuator Orientation Side Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP60 - Dust Tight Features -	Category	Switches
SeriesKSLCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 32VDCActuator TypeStandardMounting TypeThrough Hole, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle11.10mmActuator OrientationSide ActuatedTermination StylePC PinOutline7.40mm x 7.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP60 - Dust TightFeatures-		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 32VDCActuator TypeStandardMounting TypeThrough Hole, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle11.10mmActuator OrientationSide ActuatedTermination StylePC PinOutline7.40mm x 7.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP60 - Dust TightFeatures-	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Through Hole, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle 11.10mm Actuator Orientation Side Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 130gf Ingress Protection IP60 - Dust Tight Features	Series	KSL
Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Through Hole, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle 11.10mm Actuator Orientation Side Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP60 - Dust Tight Features -	Circuit	SPST-NO
Actuator Type Standard Mounting Type Through Hole, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle 11.10mm Actuator Orientation Side Actuated Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP60 - Dust Tight Features -	Switch Function	Off-Mom
Mounting TypeThrough Hole, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle11.10mmActuator OrientationSide ActuatedTermination StylePC PinOutline7.40mm x 7.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP60 - Dust TightFeatures-	Contact Rating @ Voltage	0.01A @ 32VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle 11.10mm Actuator Orientation Side Actuated PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 130gf Ingress Protection Features	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Side Actuated PC Pin Outline 7.40mm x 7.40mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Ing	Mounting Type	Through Hole, Right Angle
Actuator Orientation Side Actuated PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 130gf Ingress Protection IP60 - Dust Tight Features -	Actuator Height off PCB, Vertical	-
Termination Style PC Pin Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP60 - Dust Tight Features -	Actuator Length, Right Angle	11.10mm
Outline 7.40mm x 7.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection IP60 - Dust Tight Features -	Actuator Orientation	Side Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP60 - Dust TightFeatures-	Termination Style	PC Pin
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP60 - Dust TightFeatures-	Outline	7.40mm x 7.40mm
Illumination Voltage (Nominal)-Operating Force130gfIngress ProtectionIP60 - Dust TightFeatures-	Illumination	Non-Illuminated
Operating Force 130gf Ingress Protection IP60 - Dust Tight Features -	Illumination Type, Color	-
Ingress Protection IP60 - Dust Tight Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	130gf
	Ingress Protection	IP60 - Dust Tight
Report errors?	Features	-
		Report errors?

KSL0V331 LFTR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KSL0V331 LFTR Payment Methods



















KSL0V331 LFTR Shipping Methods













If you have any question about KSL0V331 LFTR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com