



KT11P3SA2M33 Information

Heisener.com

Part Number KT11P3SA2M33

Manufacturer C&K **Category** Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 1VA 50V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KT11P3SA2M33 Specifications

Manufacturer Part Number KT11P3SA2M33 Manufacturer C&K Category Switches Package - Series KT Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage IVA @ 50VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Height Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed		
CategorySwitchesPackage-SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage1VA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Manufacturer Part Number	KT11P3SA2M33
Package - Series KT Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage IVA @ 50VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Manufacturer	C&K
Package - Series KT Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 1VA @ 50VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Category	Switches
SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage1VA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ VoltageIVA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Package	-
Switch Function Contact Rating @ Voltage 1VA @ 50VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Sealed	Series	KT
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features Sealed	Circuit	SPST-NO
Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Iype, Color Illumination Type, Color Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Standard Standard Standard Standard Standard Standard Standard Standard Autuator Height Angle - Standard Standard Standard Standard Standard Standard Autuator Height Angle - Stale Actuated Flatuated Stale Actuated Flatuated Stale Actuated Flatuated Stale Actuated Flatuated F	Switch Function	Off-Mom
Mounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Contact Rating @ Voltage	1VA @ 50VAC/DC
Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features Sealed	Mounting Type	Surface Mount, Right Angle
Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Actuator Height off PCB, Vertical	-
Termination Style Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Actuator Length, Right Angle	-
Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Actuator Orientation	Side Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Termination Style	Gull Wing
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Outline	7.11mm x 6.30mm
Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Illumination	Non-Illuminated
Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Illumination Type, Color	-
Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Illumination Voltage (Nominal)	-
Features Sealed	Operating Force	300gf
	Ingress Protection	IP57 - Dust Protected, Waterproof
Report errors?	Features	Sealed
		Report errors?

KT11P3SA2M33 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KT11P3SA2M33 Payment Methods



















KT11P3SA2M33 Shipping Methods













If you have any question about KT11P3SA2M33, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com