



KT11P4SA2M33 Information



For Reference Only

Part Number KT11P4SA2M33

Manufacturer C&K

Category Switches
Tactile Switches

Description SWITCH TACTILE SPST-NO 1VA 50V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KT11P4SA2M33 Specifications

Manufacturer Part Number KT1 IP4SA2M33 Manufacturer C&K Category Switches Package - Series KT Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage IVA @ 50VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.60mm x 6.60mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed		
CategorySwitchesPackage-SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ VoltageIVA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline6.60mm x 6.60mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Manufacturer Part Number	KT11P4SA2M33
Package - Series KT Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage IVA @ 50VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Side Actuated Termination Style Gull Wing Outline 6.60mm x 6.60mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features KT KT KT KT KT KT KT KT KT K	Manufacturer	C&K
Package-SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage1VA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline6.60mm x 6.60mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Category	Switches
SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage1VA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline6.60mm x 6.60mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage1VA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline6.60mm x 6.60mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Package	-
Switch Function Contact Rating @ Voltage 1VA @ 50VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.60mm x 6.60mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Sealed	Series	KT
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Outline G.60mm x 6.60mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Standard Standard Surface Mount, Right Angle - Character Mount, Right Angle - Side Actuated Cull Wing Gull Wing Outline 6.60mm x 6.60mm 100mm x 6.60mm Character Mount, Right Angle - Side Actuated Side	Circuit	SPST-NO
Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.60mm x 6.60mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Standard Standard Standard Standard Standard Standard Standard Non-Ille - 300gf IP57 - Dust Protected, Waterproof Sealed	Switch Function	Off-Mom
Mounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline6.60mm x 6.60mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Contact Rating @ Voltage	1VA @ 50VAC/DC
Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.60mm x 6.60mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.60mm x 6.60mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Mounting Type	Surface Mount, Right Angle
Actuator Orientation Side Actuated Termination Style Gull Wing Outline 6.60mm x 6.60mm Illumination Non-Illuminated Illumination Type, Color	Actuator Height off PCB, Vertical	-
Termination Style Outline 6.60mm x 6.60mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Actuator Length, Right Angle	-
Outline 6.60mm x 6.60mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Actuator Orientation	Side Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Termination Style	Gull Wing
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Outline	6.60mm x 6.60mm
Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Illumination	Non-Illuminated
Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Illumination Type, Color	-
Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Illumination Voltage (Nominal)	-
Features Sealed	Operating Force	300gf
	Ingress Protection	IP57 - Dust Protected, Waterproof
Report errors?	Features	Sealed
		Report errors?

KT11P4SA2M33 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KT11P4SA2M33 Payment Methods



















KT11P4SA2M33 Shipping Methods













If you have any question about KT11P4SA2M33, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com