

## KT11P4SA2M34LFS

### **KT11P4SA2M34LFS Information**



For Reference Only

Part Number KT11P4SA2M34LFS

**Manufacturer** C&K **Category** Switches

**Description** SWITCH TACTILE SPST-NO 1VA 32V

**Tactile Switches** 

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## KT11P4SA2M34LFS Specifications

Manufacturer Part Number     KT11P4SA2M34LFS       Manufacturer     C&K       Category     Switches       Package     -       Series     KT       Circuit     SPST-NO       Switch Function     Off-Mom       Contact Rating @ Voltage     1VA @ 32VAC/DC       Actuator Type     Standard       Mounting Type     Surface Mount, Right Angle       Actuator Height off PCB, Vertical     -       Actuator Length, Right Angle     -       Actuator Orientation     Side Actuated       Termination Style     Gull Wing       Outline     7.11mm x 6.30mm       Illumination     Non-Illuminated       Illumination Type, Color     -       Illumination Voltage (Nominal)     -       Operating Force     300gf       Ingress Protection     IP57 - Dust Protected, Waterproof       Features     Sealed		
CategorySwitchesPackage-SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage1VA @ 32VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, Waterproof	Manufacturer Part Number	KT11P4SA2M34LFS
Package - Series KT Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage IVA @ 32VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof	Manufacturer	C&K
Package-SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ VoltageIVA @ 32VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, Waterproof	Category	Switches
SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage1VA @ 32VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, Waterproof		Tactile Switches
Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 1VA @ 32VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof	Package	-
Switch Function Contact Rating @ Voltage 1VA @ 32VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof	Series	KT
Contact Rating @ Voltage 1VA @ 32VAC/DC Actuator Type Standard  Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical  Actuator Length, Right Angle  - Actuator Orientation Side Actuated  Termination Style Gull Wing  Outline 7.11mm x 6.30mm  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force 300gf  Ingress Protection IP57 - Dust Protected, Waterproof	Circuit	SPST-NO
Actuator Type Standard  Mounting Type Surface Mount, Right Angle  Actuator Height off PCB, Vertical  Actuator Length, Right Angle  Actuator Orientation Side Actuated  Termination Style Gull Wing  Outline 7.11mm x 6.30mm  Illumination Type, Color  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force 300gf  Ingress Protection IP57 - Dust Protected, Waterproof	Switch Function	Off-Mom
Mounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, Waterproof	Contact Rating @ Voltage	1VA @ 32VAC/DC
Actuator Height off PCB, Vertical  Actuator Length, Right Angle  Actuator Orientation  Side Actuated  Termination Style  Gull Wing  Outline  7.11mm x 6.30mm  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force  Ingress Protection	Actuator Type	Standard
Actuator Length, Right Angle  Actuator Orientation  Side Actuated  Termination Style  Gull Wing  Outline  7.11mm x 6.30mm  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Operating Force  300gf  Ingress Protection  Ingress Protection   Ingress Protection  Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection   Ingress Protection	Mounting Type	Surface Mount, Right Angle
Actuator Orientation Side Actuated  Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof	Actuator Height off PCB, Vertical	-
Termination Style  Outline  7.11mm x 6.30mm  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Operating Force  300gf  Ingress Protection  Gull Wing  7.11mm x 6.30mm  Non-Illuminated  -  Illuminated  Illuminated  Illumination Voltage (Nominal)  Ingress Protection  IP57 - Dust Protected, Waterproof	Actuator Length, Right Angle	-
Outline 7.11mm x 6.30mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Operating Force 300gf  Ingress Protection IP57 - Dust Protected, Waterproof	Actuator Orientation	Side Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, Waterproof	Termination Style	Gull Wing
Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof	Outline	7.11mm x 6.30mm
Illumination Voltage (Nominal)       -         Operating Force       300gf         Ingress Protection       IP57 - Dust Protected, Waterproof	Illumination	Non-Illuminated
Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof	Illumination Type, Color	-
Ingress Protection IP57 - Dust Protected, Waterproof	Illumination Voltage (Nominal)	-
	Operating Force	300gf
Features Sealed	Ingress Protection	IP57 - Dust Protected, Waterproof
	Features	Sealed
Report errors?		Report errors?

#### **KT11P4SA2M34LFS Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KT11P4SA2M34LFS Payment Methods**



















## KT11P4SA2M34LFS Shipping Methods













If you have any question about KT11P4SA2M34LFS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com