



## **KT11P4SA3M33 Information**



For Reference Only

Part Number KT11P4SA3M33

**Manufacturer** C&K **Category** Switches

Tactile Switches

**Description** SWITCH TACTILE SPST-NO 1VA 50V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KT11P4SA3M33 Specifications**

Manufacturer Part Number         KT11P4SA3M33           Manufacturer         C&K           Category         Switches           Package         -           Series         KT           Circuit         SPST-NO           Switch Function         Off-Mom           Cotact Rating @ Voltage         1VA @ 50VAC/DC           Actuator Type         Standard           Mounting Type         Surface Mount, Right Angle           Actuator Height off PCB, Vertical         -           Actuator Unitation Fight Angle         -           Actuator Orientation         Side Actuated           Termination Style         Gull Wing           Outline         7.11mm x 6.30mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Operating Force         300gf           Ingress Protection         IP57 - Dust Protected, Waterproof           Features         Sealed		
CategorySwitchesPackage-SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage1VA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Manufacturer Part Number	KT11P4SA3M33
Package - Series KT Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage IVA @ 50VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical - Actuator Length, Right Angle Actuator United Style Gull Wing Outline Style Gull Wing Outline 7.11mm x 6.30mm Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 300gf Ingress Protection IP57 - Dust Protected, Waterproof Features SPST-NO SPS	Manufacturer	C&K
Package-SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ VoltageIVA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Category	Switches
SeriesKTCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ VoltageIVA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage1VA @ 50VAC/DCActuator TypeStandardMounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Package	-
Switch Function Contact Rating @ Voltage 1VA @ 50VAC/DC Actuator Type Standard Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Gull Wing Outline 7.11mm x 6.30mm Illumination Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Sealed	Series	KT
Contact Rating @ Voltage Actuator Type Standard  Mounting Type Surface Mount, Right Angle Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style Outline Outline 7.11mm x 6.30mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Standard Surface Mount, Right Angle - Character Mount, Right Angle - Surface Mount, Right Angle - Side Actuated - Sull Wing - Sull Wing - Sull Wing - Sundard - Side Actuated	Circuit	SPST-NO
Actuator Type Standard  Mounting Type Surface Mount, Right Angle  Actuator Height off PCB, Vertical  Actuator Length, Right Angle  - Actuator Orientation Side Actuated  Termination Style Gull Wing  Outline 7.11mm x 6.30mm  Illumination Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force 300gf  Ingress Protection IP57 - Dust Protected, Waterproof  Features  Standard  Standard  Standard  Standard  Standard  Standard  Standard  Standard  Standard  Actuator Mount, Right Angle  -  Surface Mount, Right Angle  -  Standard  Standard  Standard  -  Standard  Standard  -  Standard  Standard  -  Standard  -  Standard  Standard  -  Standard  Standard  -  Standard  Standard  -  Standard  S	Switch Function	Off-Mom
Mounting TypeSurface Mount, Right AngleActuator Height off PCB, Vertical-Actuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleGull WingOutline7.11mm x 6.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Contact Rating @ Voltage	1VA @ 50VAC/DC
Actuator Height off PCB, Vertical  Actuator Length, Right Angle  Actuator Orientation  Side Actuated  Termination Style  Gull Wing  Outline  7.11mm x 6.30mm  Illumination  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force  300gf  Ingress Protection  IP57 - Dust Protected, Waterproof  Features  Sealed	Actuator Type	Standard
Actuator Length, Right Angle  Actuator Orientation  Side Actuated  Termination Style  Gull Wing  Outline  7.11mm x 6.30mm  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Operating Force  300gf  Ingress Protection  IP57 - Dust Protected, Waterproof  Features  Sealed	Mounting Type	Surface Mount, Right Angle
Actuator Orientation Side Actuated  Gull Wing Outline 7.11mm x 6.30mm Illumination Non-Illuminated Illumination Type, Color	Actuator Height off PCB, Vertical	-
Termination Style  Outline  7.11mm x 6.30mm  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Operating Force  300gf  Ingress Protection  IP57 - Dust Protected, Waterproof  Features  Sealed	Actuator Length, Right Angle	-
Outline 7.11mm x 6.30mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Operating Force 300gf  Ingress Protection IP57 - Dust Protected, Waterproof  Features Sealed	Actuator Orientation	Side Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Termination Style	Gull Wing
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Outline	7.11mm x 6.30mm
Illumination Voltage (Nominal)       -         Operating Force       300gf         Ingress Protection       IP57 - Dust Protected, Waterproof         Features       Sealed	Illumination	Non-Illuminated
Operating Force300gfIngress ProtectionIP57 - Dust Protected, WaterproofFeaturesSealed	Illumination Type, Color	-
Ingress Protection IP57 - Dust Protected, Waterproof Features Sealed	Illumination Voltage (Nominal)	-
Features Sealed	Operating Force	300gf
	Ingress Protection	IP57 - Dust Protected, Waterproof
Report errors?	Features	Sealed
		Report errors?

#### **KT11P4SA3M33 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KT11P4SA3M33 Payment Methods**





















## **KT11P4SA3M33 Shipping Methods**













If you have any question about KT11P4SA3M33, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com