

KTK-2-1/2 Information



For Reference Only

Part Number KTK-2-1/2 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 2.5A 600VAC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KTK-2-1/2 Specifications

Manufacturer Part Number KTK-2-1/2 Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series KTK Fuse Type Cartridge Current Rating 2.5A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesKTKFuse TypeCartridgeCurrent Rating2.5AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer Part Number	KTK-2-1/2
Package 5AG, 10mm x 38.1mm Series KTK Fuse Type Cartridge Current Rating 2.5A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 10.00kA	Manufacturer	Eaton
Package 5AG, 10mm x 38.1mm Series KTK Fuse Type Cartridge Current Rating 2.5A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesKTKFuse TypeCartridgeCurrent Rating2.5AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating2.5AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 2.5A 600V - CSA, UL - COVA Fast Fast Fast Fast CSA, UL CSA, UL CSA, UL COVA Holder Fackage / Case SAG, 10mm x 38.1mm O.406" Dia x 1.500" L (10.30mm x 38.10mm)	Series	KTK
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Response Time Fast Fast Fast Fast Foat Approvals - CSA, UL Oberating Temperature Fackage / Case Fackage / Case Fackage / Case Fackage / Case Fackage / Dimension - Response Time Fast Fast	Current Rating	2.5A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Fast Electrical, Industrial - CSA, UL	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - DC	-
Features - Class - CSA, UL Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Fast
Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Electrical, Industrial
Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CSA, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
		Report errors?

KTK-2-1/2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KTK-2-1/2 Payment Methods



















KTK-2-1/2 Shipping Methods













If you have any question about KTK-2-1/2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com