



Heisener.com

## KTPS05-03315U-VI-P2 Information

Part Number KTPS05-03315U-VI-P2

Manufacturer Volgen America/Kaga Electronics USA

**Category** Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** 3.3V/1.5 AMP 5W WALL ADAPTER DOE

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# KTPS05-03315U-VI-P2 Specifications

Manufacturer Part NumberKTPS05-03315U-VI-P2ManufacturerVolgen America/Kaga Electronics USACategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesKTPS05Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output3.3VCurrent - Output (Max)1.5APower (Watts)5WNo Load Power Consumption-ApplicationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         KTPS05           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         3.3V           Current - Output (Max)         1.5A           Power (Watts)         5W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Manufacturer Part Number	KTPS05-03315U-VI-P2
Package         -           Series         KTPS05           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         3.3V           Current - Output (Max)         1.5A           Power (Watts)         5W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package         -           Series         KTPS05           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         3.3V           Current - Output (Max)         1.5A           Power (Watts)         5W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesKTPS05Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $3.3\text{ V}$ Current - Output (Max) $1.5\text{ A}$ Power (Watts) $5\text{ W}$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.5\text{mm I.D. x } 5.5\text{mm O.D. x } 9.5\text{mm}$ Size / Dimension $2.20^{\circ}\text{ L x } 1.10^{\circ}\text{ W x } 1.65^{\circ}\text{ H } (56.0\text{mm x } 28.0\text{mm x } 42.0\text{mm})$		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 3.3V Current - Output (Max) 1.5A Power (Watts) 5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Package	-
Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         3.3V           Current - Output (Max)         1.5A           Power (Watts)         5W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Series	KTPS05
Input Type Fixed Blade  Voltage - Input 100 ~ 240 VAC  Voltage - Output 3.3V  Current - Output (Max) 1.5A  Power (Watts) 5W  No Load Power Consumption - Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Region Utilized	North America
Voltage - Input  100 ~ 240 VAC  Voltage - Output  3.3V  Current - Output (Max)  1.5A  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  100 ~ 240 VAC  3.3V  1.5A  Power (Watts)  5W  No Load Power Consumption  -  Positive Center  ITE (Commercial)  Level VI  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Form	Wall Mount
Voltage - Output  3.3V  Current - Output (Max)  1.5A  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.3V  1.5A  1.5A  Power (Watts)  Level Center  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Input Type	Fixed Blade
Current - Output (Max)  1.5A  Power (Watts)  5W  No Load Power Consumption  - Polarization  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  1.5A  1.5A  1.5A  1.5A  1.5A  1.5A  2.84  5W  0.04  1.55  1.54  1.55  1.54  1.54  1.55  1.55  1.5	Voltage - Input	100 ~ 240 VAC
Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Voltage - Output	3.3V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}$ C ~ $40^{\circ}$ COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $2.20^{\circ}$ L x $1.10^{\circ}$ W x $1.65^{\circ}$ H ( $56.0$ mm x $28.0$ mm x $42.0$ mm)	Current - Output (Max)	1.5A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $2.20^{\circ}\text{L x } 1.10^{\circ}\text{W x } 1.65^{\circ}\text{H } (56.0 \text{mm x } 28.0 \text{mm x } 42.0 \text{mm})$	Power (Watts)	5W
Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	No Load Power Consumption	-
Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.20^{\circ}\text{L x }1.10^{\circ}\text{W x }1.65^{\circ}\text{H }(56.0\text{mm x }28.0\text{mm x }42.0\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Efficiency	Level VI
Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)
10ps/ 511015/		Report errors?

### KTPS05-03315U-VI-P2 Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## KTPS05-03315U-VI-P2 Payment Methods



















# KTPS05-03315U-VI-P2 Shipping Methods













If you have any question about KTPS05-03315U-VI-P2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com