



Heisener.com

KTPS05-05015U-VI-P3 Information

Part Number KTPS05-05015U-VI-P3

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 8W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KTPS05-05015U-VI-P3 Specifications

Manufacturer Part Number KTPS05-05015U-VI-P3 Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) Package - Series KTPS05 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 5V Current - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesKTPS05Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)1.5APower (Watts)7.5WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Manufacturer Part Number	KTPS05-05015U-VI-P3
Package - Series KTPS05 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector KTPS05 Archive America KTPS05 KTP	Manufacturer	Volgen America/Kaga Electronics USA
Package-SeriesKTPS05Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)1.5APower (Watts)7.5WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Category	Power Supplies - External/Internal (Off-Board)
SeriesKTPS05Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $1.5A$ Power (Watts) $7.5W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug, 1.35 mm I.D. $x 3.5$ mm O.D. $x 9.5$ mm		AC DC Desktop, Wall Adapters
Region Utilized Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Series	KTPS05
Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Fixed Blade 5V Current - Output Onactor For Cado VAC Substitute Center Fixed Blade 5V Current - Output (Max) 1.5A Power (Watts) 7.5W Fixed Blade 5V Current - Output (Max) 1.5A Fixed Blade 6V Fix	Region Utilized	North America
Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $1.5A$ Power (Watts) $7.5W$ No Load Power Consumption $-$ Polarization $Positive Center$ Applications $ITE (Commercial)$ Efficiency $Level VI$ Operating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output Connector $Barrel Plug, 1.35mm I.D. \times 3.5mm O.D. \times 9.5mm$	Form	Wall Mount
Voltage - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 7.5W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Voltage - Input	100 ~ 240 VAC
Power (Watts) $7.5W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug, 1.35 mm I.D. x 3.5 mm O.D. x 9.5 mm	Voltage - Output	5V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Current - Output (Max)	1.5A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Power (Watts)	7.5W
ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	No Load Power Consumption	-
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Applications	ITE (Commercial)
Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm	Efficiency	Level VI
	Operating Temperature	0°C ~ 40°C
Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Output Connector	Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 9.5mm
	Size / Dimension	2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)
Report errors?		Report errors?

KTPS05-05015U-VI-P3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KTPS05-05015U-VI-P3 Payment Methods





















KTPS05-05015U-VI-P3 Shipping Methods













If you have any question about KTPS05-05015U-VI-P3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com