



Heisener.com

KTPS05-07510U-VI-P2 Information

Part Number KTPS05-07510U-VI-P2

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 7.5V 8W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KTPS05-07510U-VI-P2 Specifications

Manufacturer Part Number KTPS05-07510U-VI-P2 Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series KTPS05 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 1A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series KTPS05 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 1A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Manufacturer Part Number	KTPS05-07510U-VI-P2
Package - Series KTPS05 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5 V Current - Output (Max) 1A Power (Watts) 7.5 W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package - Series KTPS05 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 1A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesKTPS05Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 7.5V Current - Output (Max) $1A$ Power (Watts) 7.5W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.5\text{mm I.D. x } 5.5\text{mm } 0.D. x 9.5\text{mm}$ Size / Dimension $2.20^{\circ}\text{ L x } 1.10^{\circ}\text{ W x } 1.65^{\circ}\text{ H } (56.0\text{mm x } 28.0\text{mm x } 42.0\text{mm})$		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 1A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 7.5V Current - Output (Max) $1A$ Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, $2.5\text{mm} \text{ I.D. x } 5.5\text{mm} \text{ O.D. x } 9.5\text{mm}$ Size / Dimension $2.20^{\circ}\text{ L x } 1.10^{\circ}\text{ W x } 1.65^{\circ}\text{ H } (56.0\text{mm x } 28.0\text{mm x } 42.0\text{mm})$	Series	KTPS05
Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 1A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Region Utilized	North America
Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 1A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 100 ~ 240 VAC	Form	Wall Mount
Voltage - Output (Max) 1A Power (Watts) 7.5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 7.5W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) 7.5W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Voltage - Output	7.5V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 2.20° L x 1.10° W x 1.65° H $(56.0$ mm x 28.0 mm x 42.0 mm)	Current - Output (Max)	1A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Power (Watts)	7.5W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	No Load Power Consumption	-
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Efficiency	Level VI
Size / Dimension 2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.20" L x 1.10" W x 1.65" H (56.0mm x 28.0mm x 42.0mm)
		Report errors?

KTPS05-07510U-VI-P2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KTPS05-07510U-VI-P2 Payment Methods



















KTPS05-07510U-VI-P2 Shipping Methods













If you have any question about KTPS05-07510U-VI-P2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com