

KTPS10-09012WA

KTPS10-09012WA Information

	www.halsener.com	 KTPS10-09012WA Volgen America/Kaga Electronics USA Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC WALL MOUNT ADAPTER 9V 11W - For the pricing/inventory/lead time, please contact	
	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



KTPS10-09012WA Specifications

Manufacturer Part Number KTPS10-09012WA Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC DC Desktop, Wall Adapters Package - Series KTPS10 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 9V Ourrent - Output (Max) 12A Power (Watts) 11W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 283" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesKTPS10Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input00 ~ 240 VACVoltage - Output (Max)9VCurrent - Output (Max)1.2APower (Watts)-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Manufacturer Part Number	KTPS10-09012WA
Ac DC Desktop, Wall AdaptersPackage-SeriesKTPS10Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output9VCurrent - Output (Max)1.2APower (Watts)1.1WNo Load Power Consumption-ApplicationsPositive CenterApplicationsTE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBartel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dinension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package-SeriesKTPS10Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output9VCurrent - Output (Max)1.2APower (Wats)11WNo Load Power Consumption-PolarizationSociave CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBartel Plug. 2.1mm I.D. x. 5.5mm O.D. x. 9.5mmSize / Dimension2.83" L x. 1.34" W x. 1.65" H (72.0mm x. 34.0mm x. 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series KTPS10 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 9V Current - Output (Max) 1.2A Power (Wats) 11W No Load Power Consumption - Polarization Positive Center Applications IE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barel Plug.2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 9V Current - Output (Max) 1.2A Power (Watts) 11W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Package	-
FormWall MountInput TypeFixed BladeVoltage - Input100~240 VACVoltage - Output9VCurrent - Output (Max)1.2APower (Wats)1.1WNo Load Power Consumption-PolarizationPostive CenterApplicationsITE (Commercial Science)EfficiencyIcev IVOperating Temperature0°C ~ 40°COutput ConnectorBarel Plag. Science)Size / Dimension2.83° Lx 1.34° WX 1.65° H (72.0mm x 42.0mm)	Series	KTPS10
Input TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output9VCurrent - Output (Max)1.2APower (Watts)11WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBartel Plug, 2.1 mm ILD, x 5.5 mm OLD, x 9.5 mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0 mm x 34.0 mm x 42.0 mm)	Region Utilized	North America
Proof PVoltage - Input100 ~ 240 VACVoltage - Output9VCurrent - Output (Max)1.2APower (Watts)11WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Form	Wall Mount
Voltage - Output9VCurrent - Output (Max)1.2APower (Watts)11WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Input Type	Fixed Blade
Current - Output (Max) 1.2A Power (Watts) 11W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 283" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)11WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Voltage - Output	9V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Current - Output (Max)	1.2A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Power (Watts)	11W
ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	No Load Power Consumption	-
EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Polarization	Positive Center
Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Efficiency	Level V
Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Operating Temperature	0° C ~ 40° C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)
		Report errors?

KTPS10-09012WA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

KTPS10-09012WA Payment Methods



KTPS10-09012WA Shipping Methods



If you have any question about KTPS10-09012WA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com