

KTPS12-05920WA-VI-P1

KTPS12-05920WA-VI-P1 Information

Part Number KTPS12-05920WA-VI-P1

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADPTR 5.9V 12W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KTPS12-05920WA-VI-P1 Specifications

Manufacturer Part Number KTPS12-05920WA-VI-P1 Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series KTPS12 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5.9V Current - Output (Max) 2.04A Power (Watts) 12W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series KTPS12 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5.9V Current - Output (Max) 2.04A Power (Watts) 12W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Manufacturer Part Number	KTPS12-05920WA-VI-P1	
AC DC Desktop, Wall Adapters Package Series KTPS12 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output Current - Output (Max) 12W No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension AC DC Desktop, Wall Adapters KTPS12 KTPS12 North America Vall Mount North America Vall Mount 100 ~ 240 VAC Vall Mount 100 ~ 240 VAC Voltage - Output 100 ~ 240 VAC Voltage - Input 100 ~ 240 VAC Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Manufacturer	Volgen America/Kaga Electronics USA	
Package - Series KTPS12 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5.9V Current - Output (Max) 2.04A Power (Watts) 12W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
SeriesKTPS12Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 5.9V Current - Output (Max) 2.04A Power (Watts) 12W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $2.83^{\circ}\text{ L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)}$		AC DC Desktop, Wall Adapters	
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output5.9VCurrent - Output (Max)2.04APower (Watts)12WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Package	-	
Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5.9V Current - Output (Max) 2.04A Power (Watts) 12W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 240 VAC	Series	KTPS12	
Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5.9V Current - Output (Max) Power (Watts) 12W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension Fixed Blade Fixed Blade 100 ~ 240 VAC	Region Utilized	North America	
Voltage - Input 100 ~ 240 VAC Voltage - Output 5.9V Current - Output (Max) 2.04A Power (Watts) 12W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 100 ~ 240 VAC	Form	Wall Mount	
Voltage - Output (Max) 5.9V Current - Output (Max) 2.04A Power (Watts) 12W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Input Type	Fixed Blade	
Current - Output (Max) Power (Watts) 12W No Load Power Consumption - Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Voltage - Input	100 ~ 240 VAC	
Power (Watts) 12W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Voltage - Output	5.9V	
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Current - Output (Max)	2.04A	
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Power (Watts)	12W	
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	No Load Power Consumption	-	
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Polarization	Positive Center	
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.83^{\circ}\text{L} \times 1.34^{\circ}\text{W} \times 1.65^{\circ}\text{H} (72.0\text{mm} \times 34.0\text{mm} \times 42.0\text{mm})$	Applications	ITE (Commercial)	
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Efficiency	Level VI	
Size / Dimension 2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	Operating Temperature	0°C ~ 40°C	
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm	
Report errors?	Size / Dimension	2.83" L x 1.34" W x 1.65" H (72.0mm x 34.0mm x 42.0mm)	
			Report errors?

KTPS12-05920WA-VI-P1 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KTPS12-05920WA-VI-P1 Payment Methods



















KTPS12-05920WA-VI-P1 Shipping Methods













If you have any question about KTPS12-05920WA-VI-P1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com