

# KTPS18-05030WA-VI-P2

### KTPS18-05030WA-VI-P2 Information



For Reference Only

Part Number KTPS18-05030WA-VI-P2

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 5V 18W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### KTPS18-05030WA-VI-P2 Specifications

Manufacturer Part NumberKTPS18-05030WA-VI-P2ManufacturerVolgen America/Kaga Electronics USACategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesKTPS18Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         KTPS18           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         5V           Current - Output (Max)         3A           Power (Watts)         15W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Manufacturer Part Number	KTPS18-05030WA-VI-P2
Package         -           Series         KTPS18           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         5V           Current - Output (Max)         3A           Power (Watts)         15W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package         -           Series         KTPS18           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         100 ~ 240 VAC           Voltage - Output         5V           Current - Output (Max)         3A           Power (Watts)         15W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesKTPS18Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 100 ~ 240 VAC  Voltage - Output 5V  Current - Output (Max) 3A  Power (Watts) 15W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Series	KTPS18
Input Type Fixed Blade  Voltage - Input 100 ~ 240 VAC  Voltage - Output 5V  Current - Output (Max) 3A  Power (Watts) 15W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Region Utilized	North America
Voltage - Input  100 ~ 240 VAC  Voltage - Output  5V  Current - Output (Max)  3A  Power (Watts)  15W  No Load Power Consumption  - Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  100 ~ 240 VAC	Form	Wall Mount
Voltage - Output (Max) 3A  Power (Watts) 15W  No Load Power Consumption - Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  15W  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Voltage - Output	5V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}$ C ~ $40^{\circ}$ COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $2.95$ " L x $1.41$ " W x $2.58$ " H ( $75.0$ mm x $35.8$ mm x $65.6$ mm)	Current - Output (Max)	3A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $2.95$ " L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Power (Watts)	15W
Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	No Load Power Consumption	-
Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.95^{\circ}\text{L} \times 1.41^{\circ}\text{W} \times 2.58^{\circ}\text{H} (75.0\text{mm} \times 35.8\text{mm} \times 65.6\text{mm})$	Applications	ITE (Commercial)
Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Efficiency	Level VI
Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Donort owners?	Size / Dimension	2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)
Report errors?		Report errors?

#### KTPS18-05030WA-VI-P2 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### KTPS18-05030WA-VI-P2 Payment Methods



















# KTPS18-05030WA-VI-P2 Shipping Methods













If you have any question about KTPS18-05030WA-VI-P2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com