



### KTPS200-12160-VI Information



For Reference Only

Part Number KTPS200-12160-VI

ManufacturerVolgen America/Kaga Electronics USACategoryPower Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 12V 200W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## KTPS200-12160-VI Specifications

Manufacturer Part Number         KTPS200-12160-VI           Manufacturer         Volgen America/Kaga Electronics USA           Category         Power Supplies - External/Internal (Off-Board)           Rekage         -           Series         KTPS200           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         12V           Current - Output (Max)         16A           Power (Watts)         192W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)           Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         KTPS200           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         12V           Current - Output (Max)         16A           Power (Watts)         192W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Manufacturer Part Number	KTPS200-12160-VI
Package         -           Series         KTPS200           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         12V           Current - Output (Max)         16A           Power (Watts)         192W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package         -           Series         KTPS200           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         12V           Current - Output (Max)         16A           Power (Watts)         192W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesKTPS200Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $12\text{V}$ Current - Output (Max) $16\text{A}$ Power (Watts) $192\text{W}$ No Load Power Consumption-Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $7.20^{\circ}\text{L x 3.19}^{\circ}\text{W x 1.67}^{\circ}\text{H (183.0mm x 81.0mm x 42.3mm)}$		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 16A Power (Watts) 192W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 1.20	Package	-
FormDesktop (Class I)Input Type $Cord$ (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $12V$ Current - Output (Max) $16A$ Power (Watts) $192W$ No Load Power Consumption-Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorPower DIN, 4 PinSize / Dimension $7.20^{\circ}L \times 3.19^{\circ}W \times 1.67^{\circ}H$ (183.0mm x 81.0mm x 42.3mm)	Series	KTPS200
Input Type Cord (Sold Separately)  Voltage - Input 100 ~ 240 VAC  Voltage - Output 12V  Current - Output (Max) 16A  Power (Watts) 192W  No Load Power Consumption -  Polarization -  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Region Utilized	International
Voltage - Input  100 ~ 240 VAC  Voltage - Output  12V  Current - Output (Max)  16A  Power (Watts)  192W  No Load Power Consumption  - Polarization  - Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  12V  16A  192W  192W	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  16A  Power (Watts)  No Load Power Consumption  Polarization  - Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Power DIN, 4 Pin  7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  16A  Power (Watts)  192W  No Load Power Consumption  - Polarization  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  16A  192W  192W  - Value (Max)  - Value (Max)  192W  - Value (Max)  192W  - Value (Max)  -	Voltage - Input	100 ~ 240 VAC
Power (Watts)  192W  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Voltage - Output	12V
No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Current - Output (Max)	16A
Polarization - Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Power (Watts)	192W
Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	No Load Power Consumption	-
Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $7.20^{\circ}\text{L x } 3.19^{\circ}\text{W x } 1.67^{\circ}\text{H } (183.0\text{mm x } 81.0\text{mm x } 42.3\text{mm})$	Applications	ITE (Commercial)
Output Connector Power DIN, 4 Pin Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Efficiency	Level VI
Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)
		Report errors?

### KTPS200-12160-VI Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### KTPS200-12160-VI Payment Methods



















### KTPS200-12160-VI Shipping Methods













If you have any question about KTPS200-12160-VI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com