



### KTPS200-19105-VI Information



For Reference Only

Part Number KTPS200-19105-VI

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-I

Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 19V 200W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## KTPS200-19105-VI Specifications

| Manufacturer Part Number         KTPS200-19105-VI           Manufacturer         Volgen America/Kaga Electronics USA           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         KTPS200           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         19V           Current - Output (Max)         10.5A           Power (Watts)         200W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)  |                           |   |
|--|---------------------------|---|
| Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         KTPS200           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         19V           Current - Output (Max)         10.5A           Power (Watts)         200W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Manufacturer Part Number  | KTPS200-19105-VI  |
| AC DC Desktop, Wall Adapters  Package Series KTPS200 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 100 ~ 240 VAC  Voltage - Output 19V Current - Output (Max) 10.5A Power (Watts) 200W  No Load Power Consumption - Polarization ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension  AC DC Desktop, Wall Adapters  KTPS200 Internation International Inte | Manufacturer              | Volgen America/Kaga Electronics USA                     |
| Package         -           Series         KTPS200           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         19V           Current - Output (Max)         10.5A           Power (Watts)         200W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)  | Category                  | Power Supplies - External/Internal (Off-Board)          |
| SeriesKTPS200Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output19VCurrent - Output (Max)10.5APower (Watts)200WNo Load Power Consumption-Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorPower DIN, 4 PinSize / Dimension7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   |                           | AC DC Desktop, Wall Adapters                            |
| Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         19V           Current - Output (Max)         10.5A           Power (Watts)         200W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Package                   | -   |
| Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         19V           Current - Output (Max)         10.5A           Power (Watts)         200W           No Load Power Consumption         -           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Series                    | KTPS200   |
| Input Type  Cord (Sold Separately)  Voltage - Input  100 ~ 240 VAC  Voltage - Output  19V  Current - Output (Max)  Power (Watts)  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  Cord (Sold Separately)  100 ~ 240 VAC  100 ~ 240 VAC  Current - Output (Max)  10.5A  200W  10.5A  200W  10.5A  200W   | Region Utilized           | International   |
| Voltage - Input  100 ~ 240 VAC  Voltage - Output  19V  Current - Output (Max)  10.5A  Power (Watts)  No Load Power Consumption  Polarization  - Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Form                      | Desktop (Class I)                                       |
| Voltage - Output (Max) 10.5A  Power (Watts) 200W  No Load Power Consumption -  Polarization -  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Input Type                | Cord (Sold Separately)                                  |
| Current - Output (Max)  Power (Watts)  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  O°C ~ 40°C  Output Connector  Power DIN, 4 Pin  7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Voltage - Input           | 100 ~ 240 VAC   |
| Power (Watts)  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  O°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  200W  Consumption  -  Consumption  Note: The power of | Voltage - Output          | 19V   |
| No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  O°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)  | Current - Output (Max)    | 10.5A   |
| Polarization - Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Power (Watts)             | 200W  |
| Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)  | No Load Power Consumption | -   |
| Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Polarization              | -   |
| Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Applications              | ITE (Commercial)  |
| Output Connector Power DIN, 4 Pin Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Efficiency                | Level VI  |
| Size / Dimension 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm)   | Operating Temperature     | 0°C ~ 40°C  |
|  | Output Connector          | Power DIN, 4 Pin  |
|  | Size / Dimension          | 7.20" L x 3.19" W x 1.67" H (183.0mm x 81.0mm x 42.3mm) |
| Report errors?   |                           | Report errors?  |

#### KTPS200-19105-VI Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## KTPS200-19105-VI Payment Methods



















## KTPS200-19105-VI Shipping Methods













If you have any question about KTPS200-19105-VI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com