

KTPS24-06035MP

KTPS24-06035MP Information

www.heisener.com	Part Number Manufacturer Category Description Package	Volgen America/Kaga Electronics USA Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC WALL MOUNT ADAPTER 6V 21W - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



KTPS24-06035MP Specifications

Manufacturer Part Number KTPS24-06035MP Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC DC Desktop, Wall Adapters Package - Series KTPS24 Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 100 ~ 240 VAC Voltage - Output 6V Current - Output (Max) 3.5A Power (Watts) 21W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)		
CategoryPower Supplies - External/Internal (Off-Board) AC DC Desktop, Wall AdaptersPackage-SeriesKTPS24Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output (Max)3.5APower (Watts)21WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBartel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Manufacturer Part Number	KTPS24-06035MP
AC DC bestop, Wall Adapters Package - Series KTPS24 Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 3.5A Power (Watts) 21W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package-SeriesKTPS24Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output6VCurrent - Output (Max)3.5APower (Watts)21WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBartel Plug.2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series KTPS24 Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 100 ~ 240 VAC Voltage - Output 6V Current - Output (Max) 3.5A Power (Watts) 21W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dinension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output6VCurrent - Output (Max)3.5APower (Watts)21WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm x 40.5mm)Size / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Package	-
FormWall MountInput TypeMult-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output6VCurrent - Output (Max)3.5APower (Watts)21WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyUeve VOperating Temperature0°C ~ 40°COutput ConnectorBartel Plug, 2.1mm I.D. x. 5.5mm O.D. x. 9.5mm, x. 40.5mm, s.	Series	KTPS24
Innut TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output6VCurrent - Output (Max)3.5APower (Watts)21WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Region Utilized	International
Voltage - Input100 ~ 240 VACVoltage - Output6VCurrent - Output (Max)3.5APower (Watts)21WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm x 40.5mm)Size / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Form	Wall Mount
Voltage - Output6VCurrent - Output (Max)3.5APower (Watts)21WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Input Type	Multi-Blade (Included)
Current - Output (Max)3.5APower (Watts)21WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)21WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Voltage - Output	6V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Current - Output (Max)	3.5A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Power (Watts)	21W
ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	No Load Power Consumption	-
EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Polarization	Positive Center
Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Efficiency	Level V
Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Operating Temperature	0° C ~ 40° C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)
		Report errors?

KTPS24-06035MP Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

KTPS24-06035MP Payment Methods



KTPS24-06035MP Shipping Methods



If you have any question about KTPS24-06035MP, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com