

Heisener.com

KTPS24-07530WA-VI-P1R

KTPS24-07530WA-VI-P1R Information

Part Number KTPS24-07530WA-VI-P1R

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADPTR 7.5V 24W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KTPS24-07530WA-VI-P1R Specifications

Manufacturer Part Number KTPS24-07530WA-VI-P1R Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series KTPS24 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5 V Current - Output (Max) 3A Power (Watts) 23W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series KTPS24 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 3A Power (Watts) 23W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Manufacturer Part Number	KTPS24-07530WA-VI-P1R
Package - Series KTPS24 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5 V Current - Output (Max) 3A Power (Watts) 23W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package - Series KTPS24 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5 V Current - Output (Max) 3A Power (Watts) 23W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesKTPS24Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 7.5V Current - Output (Max) 3A Power (Watts) 23W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $2.95^{\circ}\text{L} \times 1.41^{\circ}\text{W} \times 2.58^{\circ}\text{H} (75.0mm x 35.8mm x 65.6mm)$		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output7.5VCurrent - Output (Max)3APower (Watts)23WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 7.5V Current - Output (Max) 3A Power (Watts) 23W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, $2.5\text{mm} \text{ I.D. x } 5.5\text{mm} \text{ O.D. x } 9.5\text{mm}$ Size / Dimension $2.95^{\circ}\text{ L x } 1.41^{\circ}\text{ W x } 2.58^{\circ}\text{ H } (75.0\text{mm x } 35.8\text{mm x } 65.6\text{mm})$	Series	KTPS24
Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 3A Power (Watts) 23W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Region Utilized	North America
Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 3A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 100 ~ 240 VAC 7.5V 7.5V 7.5V 7.5V 7.5V 8 A A A B Current - Output (Max) A A A A B Current - Output (Max) A A A A B Current - Output (Max) A A A A B Current - Output (Max) A A A A B Current - Output (Max) A A A A A A A B Current - Output (Max) A A A A B Current - Output (Max) A A A A B Current - Output (Max) A A A A B Current - Output (Max) A A A A B Current - Output (Max) A A A A A A B Current - Output (Max) A A A A A A B Current - Output (Max) A A A A A B Current - Output (Max) A A A A A A A A A A A A A	Form	Wall Mount
Voltage - Output (Max) Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 7.5V 7.5V 7.5V 7.5V 7.5V 7.5V 8 A A A A B Current - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 23W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Voltage - Output	7.5V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 2.95 " L x 1.41 " W x 2.58 " H (75.0 mm x 35.8 mm x 65.6 mm)	Current - Output (Max)	3A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Power (Watts)	23W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	No Load Power Consumption	-
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.95^{\circ}\text{L} \times 1.41^{\circ}\text{W} \times 2.58^{\circ}\text{H} (75.0\text{mm} \times 35.8\text{mm} \times 65.6\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Efficiency	Level VI
Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)
		Report errors?

KTPS24-07530WA-VI-P1R Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KTPS24-07530WA-VI-P1R Payment Methods



















KTPS24-07530WA-VI-P1R Shipping Methods













If you have any question about KTPS24-07530WA-VI-P1R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com