



KTPS24-48005WA-VI-P2 Information



For Reference Only

Part Number KTPS24-48005WA-VI-P2

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 48V 24W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KTPS24-48005WA-VI-P2 Specifications

| Manufacturer Part Number KTPS24-48005WA-VI-P2 Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) Reckage - Series KTPS24 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 500mA Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) Report errors? | | |
|--|---------------------------|--|
| Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series KTPS24 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 48V Current - Output (Max) 500mA Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Manufacturer Part Number | KTPS24-48005WA-VI-P2 |
| Package - Series KTPS24 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 48V Current - Output (Max) 500mA Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Manufacturer | Volgen America/Kaga Electronics USA |
| Package - Series KTPS24 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 48V Current - Output (Max) 500mA Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Category | Power Supplies - External/Internal (Off-Board) |
| SeriesKTPS24Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $48V$ Current - Output (Max) 500mA Power (Watts) $24W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.5\text{mm I.D. x } 5.5\text{mm } 0.D. x 9.5\text{mm}$ Size / Dimension $2.95^{\circ}\text{L x } 1.41^{\circ}\text{W x } 2.58^{\circ}\text{H } (75.0\text{mm x } 35.8\text{mm x } 65.6\text{mm})$ | | AC DC Desktop, Wall Adapters |
| Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)500mAPower (Watts)24WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Package | - |
| Form Wall Mount Input Type Fixed Blade Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 48V Current - Output (Max) 500mA Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, $2.5\text{mm} \text{ I.D. x } 5.5\text{mm} \text{ O.D. x } 9.5\text{mm}$ Size / Dimension $2.95^{\circ}\text{ L x } 1.41^{\circ}\text{ W x } 2.58^{\circ}\text{ H } (75.0\text{mm x } 35.8\text{mm x } 65.6\text{mm})$ | Series | KTPS24 |
| Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 48V Current - Output (Max) 500mA Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension Fixed Blade Fixed Blade Fixed Blade Fixed Blade Fixed Blade Fixed Blade Fixed Blade For 240 VAC | Region Utilized | North America |
| Voltage - Input 100 ~ 240 VAC Voltage - Output 48V Current - Output (Max) 500mA Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 100 ~ 240 VAC | Form | Wall Mount |
| Voltage - Output 48V Current - Output (Max) 500mA Power (Watts) 24W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 48V 48V 48V Current - Output (Max) 500mA Power (Watts) Level WI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Input Type | Fixed Blade |
| Current - Output (Max) 500mA Power (Watts) 24W No Load Power Consumption - Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Voltage - Input | 100 ~ 240 VAC |
| Power (Watts) 24W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Voltage - Output | 48V |
| No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 2.95 " L x 1.41 " W x 2.58 " H $(75.0$ mm x 35.8 mm x 65.6 mm) | Current - Output (Max) | 500mA |
| Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Power (Watts) | 24W |
| Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | No Load Power Consumption | - |
| Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Polarization | Positive Center |
| Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.95^{\circ}\text{L} \times 1.41^{\circ}\text{W} \times 2.58^{\circ}\text{H} (75.0\text{mm} \times 35.8\text{mm} \times 65.6\text{mm})$ | Applications | ITE (Commercial) |
| Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Efficiency | Level VI |
| Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) | Operating Temperature | 0°C ~ 40°C |
| | Output Connector | Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm |
| Report errors? | Size / Dimension | 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm) |
| | | Report errors? |

KTPS24-48005WA-VI-P2 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KTPS24-48005WA-VI-P2 Payment Methods



















KTPS24-48005WA-VI-P2 Shipping Methods













If you have any question about KTPS24-48005WA-VI-P2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com