

KTPS65-2427DT-3P-VI-C-P1

KTPS65-2427DT-3P-VI-C-P1 Information



For Reference Only

Part Number KTPS65-2427DT-3P-VI-C-P1

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 65W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KTPS65-2427DT-3P-VI-C-P1 Specifications

Manufacturer Part Number KTPS65-2427DT-3P-VI-C-PI Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) Rekage - Series KTPS65 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series KTPS65 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer Part Number	KTPS65-2427DT-3P-VI-C-P1
Package-SeriesKTPS65Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output24VCurrent - Output (Max)2.7APower (Watts)65WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package - Series KTPS65 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesKTPS65Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{ rm I.D. x 5.5mm O.D. x 9.5mm}$ Size / Dimension $4.53^{\circ}\text{ L x 2.09^{\circ} W x 1.50^{\circ} H (115.0mm x 53.0mm x 38.0mm)}$		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Series	KTPS65
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Region Utilized	International
Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm I.D. x } 5.5\text{mm O.D. x } 9.5\text{mm}$ Size / Dimension $4.53^{\circ}\text{ L x } 2.09^{\circ}\text{ W x } 1.50^{\circ}\text{ H } (115.0\text{mm x } 53.0\text{mm x } 38.0\text{mm})$	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 2.7A Power (Watts) No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Output	24V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x 5.5 mm O.D. x 9.5 mm}$ Size / Dimension $4.53'' \text{L x 2.09'' W x 1.50'' H (115.0 mm x 53.0 mm x 38.0 mm)}$	Current - Output (Max)	2.7A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension $4.53^{\circ}\text{L x } 2.09^{\circ}\text{W x } 1.50^{\circ}\text{H } (115.0 \text{mm x } 53.0 \text{mm x } 38.0 \text{mm})$	Power (Watts)	65W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	No Load Power Consumption	-
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Efficiency	Level VI
Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)
		Report errors?

KTPS65-2427DT-3P-VI-C-P1 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KTPS65-2427DT-3P-VI-C-P1 Payment Methods





















KTPS65-2427DT-3P-VI-C-P1 Shipping Methods













If you have any question about KTPS65-2427DT-3P-VI-C-P1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com