



KUHP-11D17-24 Information



For Reference Only

Part Number KUHP-11D17-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 20A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KUHP-11D17-24 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series KUHP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC
Category Relays Power Relays, Over 2 Amps Package - Series KUHP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 240VAC - Max
Package - Series KUHP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 240VAC - Max
Package - Series KUHP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 240VAC - Max
SeriesKUHPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current51mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)20ASwitching Voltage240VAC - Max
Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 240VAC - Max
Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 240VAC - Max
Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 240VAC - Max
Coil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)20ASwitching Voltage240VAC - Max
Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 240VAC - Max
Contact Rating (Current) 20A Switching Voltage 240VAC - Max
Switching Voltage 240VAC - Max
Turn On Voltage (Max) 18 VDC
Turn Off Voltage (Min) -
Operate Time 20ms
Release Time 20ms
Features Insulation - Class B
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

KUHP-11D17-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KUHP-11D17-24 Payment Methods



















KUHP-11D17-24 Shipping Methods













If you have any question about KUHP-11D17-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com