



KUHP-1D51-110 Information



For Reference Only

Part Number KUHP-1D51-110

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 110V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KUHP-1D51-110 Specifications

Manufacturer Part NumberKUHP-1D51-110ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKUHPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage240VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesInsulation - Class B		
Category Relays Power Relays, Over 2 Amps Package - Series KUHP Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Insulation - Class B	Manufacturer Part Number	KUHP-1D51-110
Package - Series KUHP Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Insulation - Class B	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KUHP Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Insulation - Class B	Category	Relays
SeriesKUHPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage240VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesInsulation - Class B		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Insulation - Class B	Package	-
Coil Type Non Latching Coil Current 11mA Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Insulation - Class B	Series	KUHP
Coil Current Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Insulation - Class B	Relay Type	General Purpose
Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Insulation - Class B	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Insulation - Class B	Coil Current	11mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Insulation - Class B	Coil Voltage	110VDC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Insulation - Class B	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Insulation - Class B	Contact Rating (Current)	30A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Insulation - Class B	Switching Voltage	240VAC - Max
Operate Time20msRelease Time20msFeaturesInsulation - Class B	Turn On Voltage (Max)	82.5 VDC
Release Time 20ms Features Insulation - Class B	Turn Off Voltage (Min)	-
Features Insulation - Class B	Operate Time	20ms
	Release Time	20ms
Mounting Type Chassis Mount	Features	Insulation - Class B
viounting Type Chassis Would	Mounting Type	Chassis Mount
Termination Style Quick Connect - 0.250" (6.3mm)	Termination Style	Quick Connect - 0.250" (6.3mm)
Report errors?		Report errors?

KUHP-1D51-110 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KUHP-1D51-110 Payment Methods





















KUHP-1D51-110 Shipping Methods













If you have any question about KUHP-1D51-110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com