



KUIP-11D55-24 Information

Heisener.com

Part Number KUIP-11D55-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

RELAY GEN PURPOSE DPDT 10A 24V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KUIP-11D55-24 Specifications

Manufacturer Part NumberKUIP-11D55-24ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKUIPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current51mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10A
Category Relays Power Relays, Over 2 Amps Package - Series KUIP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A
Package - Series KUIP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A
Package - Series KUIP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A
Series KUIP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A
Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A
Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A
Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A
Contact Rating (Current) 10A
Switching Voltage 240VAC - Max
Turn On Voltage (Max) 18 VDC
Turn Off Voltage (Min) -
Operate Time 20ms
Release Time 15ms
Features Insulation - Class B
Mounting Type Chassis Mount
Termination Style Quick Connect - 0.187" (4.7mm)
Report errors

KUIP-11D55-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KUIP-11D55-24 Payment Methods



















KUIP-11D55-24 Shipping Methods













If you have any question about KUIP-11D55-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com