

KUIP-7A55-24 Information

Heisener.com

Part Number KUIP-7A55-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 10A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KUIP-7A55-24 Specifications

Manufacturer Part NumberKUIP-7A55-24ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKUIPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)20.4 VACTurn Off Voltage (Min)-Operate Time20msRelease Time15msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKUIPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)20.4 VACTurn Off Voltage (Min)-Operate Time20msRelease Time15msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)	Manufacturer Part Number	KUIP-7A55-24
Package - Series KUIP Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KUIP Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesKUIPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)20.4 VACTurn Off Voltage (Min)-Operate Time20msRelease Time15msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Package	-
Coil Type Non Latching Coil Current 84mA Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Series	KUIP
Coil Current84mACoil Voltage24VACContact FormDPST (2 Form A)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)20.4 VACTurn Off Voltage (Min)-Operate Time20msRelease Time15msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 24VAC Contact Form DPST (2 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Coil Current	84mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style 10A 240VAC - Max 20.4 VAC 10.1 VAC	Coil Voltage	24VAC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) - Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) 20.4 VAC Turn Off Voltage (Min) Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Switching Voltage	240VAC - Max
Operate Time 20ms Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	20.4 VAC
Release Time 15ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Operate Time	20ms
Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Release Time	15ms
Termination Style Quick Connect - 0.187" (4.7mm)	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.187" (4.7mm)
		Report errors?

KUIP-7A55-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KUIP-7A55-24 Payment Methods



















KUIP-7A55-24 Shipping Methods













If you have any question about KUIP-7A55-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com