



### **KUL-11D15D-12 Information**



For Reference Only

Part Number KUL-11D15D-12

Manufacturer TE Connectivity Potter & Brumfield Relays

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 10A 12V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KUL-11D15D-12 Specifications**

Manufacturer Part NumberKUL-11D15D-12ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKULRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time25msRelease Time25msFeaturesInsulation - Class BMounting TypeSocketable		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         KUL           Relay Type         General Purpose           Coil Type         Latching, Dual Coil           Coil Current         -           Coil Voltage         12VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         10A           Switching Voltage         240VAC - Max           Turn On Voltage (Max)         9 VDC           Turn Off Voltage (Min)         -           Operate Time         25ms           Release Time         25ms           Features         Insulation - Class B	Manufacturer Part Number	KUL-11D15D-12
Power Relays, Over 2 Amps  Package  Series  KUL  Relay Type  General Purpose  Coil Type  Latching, Dual Coil  Coil Current  -  Coil Voltage  12VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  10A  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  7 Urn Off Voltage (Min)  Operate Time  Release Time  25ms  Features  Insulation - Class B	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KUL Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 25ms Release Time 25ms Features Insulation - Class B	Category	Relays
SeriesKULRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time25msRelease Time25msFeaturesInsulation - Class B		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms Features Insulation - Class B	Package	-
Coil Type Latching, Dual Coil Coil Current - Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 25ms Release Time 25ms Features Insulation - Class B	Series	KUL
Coil Current Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 25ms Release Time 25ms Features Insulation - Class B	Relay Type	General Purpose
Coil Voltage 12VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 10A  Switching Voltage 240VAC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) -  Operate Time 25ms  Release Time 25ms  Features Insulation - Class B	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  Insulation - Class B	Coil Current	-
Contact Rating (Current)  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  Insulation - Class B	Coil Voltage	12VDC
Switching Voltage 240VAC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) - Operate Time 25ms  Release Time 25ms  Features Insulation - Class B	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  7 Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  Insulation - Class B	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  Insulation - Class B	Switching Voltage	240VAC - Max
Operate Time25msRelease Time25msFeaturesInsulation - Class B	Turn On Voltage (Max)	9 VDC
Release Time 25ms Features Insulation - Class B	Turn Off Voltage (Min)	-
Features Insulation - Class B	Operate Time	25ms
	Release Time	25ms
Mounting Type Socketable	Features	Insulation - Class B
	Mounting Type	Socketable
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
Report errors?		Report errors?

#### **KUL-11D15D-12 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KUL-11D15D-12 Payment Methods**



















## **KUL-11D15D-12 Shipping Methods**













If you have any question about KUL-11D15D-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com