



KUP-11D55-24 Information



For Reference Only

Part Number KUP-11D55-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KUP-11D55-24 Specifications

Manufacturer Part NumberKUP-11D55-24ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKUPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current51mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeaturesInsulation - Class BMounting TypeChassis Mount		
Category Relays Power Relays, Over 2 Amps Package - Series KUP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Manufacturer Part Number	KUP-11D55-24
Package - Series KUP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KUP Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Category	Relays
SeriesKUPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current51mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeaturesInsulation - Class B		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Package	-
Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Series	KUP
Coil Current 51mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Coil Current	51mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B	Coil Voltage	24VDC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B	Switching Voltage	240VAC - Max
Operate Time15msRelease Time10msFeaturesInsulation - Class B	Turn On Voltage (Max)	18 VDC
Release Time 10ms Features Insulation - Class B	Turn Off Voltage (Min)	-
Features Insulation - Class B	Operate Time	15ms
	Release Time	10ms
Mounting Type Chassis Mount	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Termination Style Quick Connect - 0.187" (4.7mm)	Termination Style	Quick Connect - 0.187" (4.7mm)
Report errors?		Report errors?

KUP-11D55-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KUP-11D55-24 Payment Methods



















KUP-11D55-24 Shipping Methods













If you have any question about KUP-11D55-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com