



KUP-14A11-120 Information



For Reference Only

Part Number KUP-14A11-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 5A 120V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KUP-14A11-120 Specifications

Manufacturer Part NumberKUP-14A11-120ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKUPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current24mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeaturesInsulation - Class BMounting TypeSocketable		
Category Relays Power Relays, Over 2 Amps Package - Series KUP Relay Type General Purpose Coil Type Non Latching Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Manufacturer Part Number	KUP-14A11-120
Package - Series KUP Relay Type General Purpose Coil Type Non Latching Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KUP Relay Type General Purpose Coil Type Non Latching Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Category	Relays
SeriesKUPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current24mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeaturesInsulation - Class B		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Package	-
Coil Type Non Latching Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Series	KUP
Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Coil Current	24mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B	Coil Voltage	120VAC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B	Switching Voltage	240VAC - Max
Operate Time15msRelease Time10msFeaturesInsulation - Class B	Turn On Voltage (Max)	102 VAC
Release Time 10ms Features Insulation - Class B	Turn Off Voltage (Min)	-
Features Insulation - Class B	Operate Time	15ms
	Release Time	10ms
Mounting Type Socketable	Features	Insulation - Class B
Modified Type	Mounting Type	Socketable
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
Report errors?		Report errors?

KUP-14A11-120 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KUP-14A11-120 Payment Methods





















KUP-14A11-120 Shipping Methods













If you have any question about KUP-14A11-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com