

## KUP93-14A13-120 Information

www.helsen.com

For Reference Only

Part Number KUP93-14A13-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 10A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **KUP93-14A13-120 Specifications**

Manufacturer Part NumberKUP93-14A13-120ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKUP93Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current24mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC, 28VDC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-Mounting TypeSocketable		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         KUP93           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         24mA           Coil Voltage         120VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         240VAC, 28VDC - Max           Turn On Voltage (Max)         102 VAC           Turn Off Voltage (Min)         -           Operate Time         15ms           Release Time         10ms           Features         -	Manufacturer Part Number	KUP93-14A13-120
Package         -           Series         KUP93           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         24mA           Coil Voltage         120VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         240VAC, 28VDC - Max           Turn On Voltage (Max)         102 VAC           Turn Off Voltage (Min)         -           Operate Time         15ms           Release Time         10ms           Features         -	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KUP93 Relay Type General Purpose Coil Type Non Latching Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC, 28VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features	Category	Relays
SeriesKUP93Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current24mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC, 28VDC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeatures-		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC, 28VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features -	Package	-
Coil Type Non Latching Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC, 28VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features -	Series	KUP93
Coil Current 24mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC, 28VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features -	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC, 28VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features -	Coil Type	Non Latching
Contact Form 3PDT (3 Form C)  Contact Rating (Current) 10A  Switching Voltage 240VAC, 28VDC - Max  Turn On Voltage (Max) 102 VAC  Turn Off Voltage (Min) -  Operate Time 15ms  Release Time 10ms  Features -	Coil Current	24mA
Contact Rating (Current)  Switching Voltage  240VAC, 28VDC - Max  Turn On Voltage (Max)  102 VAC  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  10ms  Features  -	Coil Voltage	120VAC
Switching Voltage 240VAC, 28VDC - Max  Turn On Voltage (Max) 102 VAC  Turn Off Voltage (Min) -  Operate Time 15ms  Release Time 10ms  Features -	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  10ms  Features  -	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features -	Switching Voltage	240VAC, 28VDC - Max
Operate Time 15ms Release Time 10ms Features -	Turn On Voltage (Max)	102 VAC
Release Time 10ms Features -	Turn Off Voltage (Min)	-
Features -	Operate Time	15ms
	Release Time	10ms
Mounting Type Socketable	Features	-
0 71	Mounting Type	Socketable
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
Report errors?		Report errors?

#### KUP93-14A13-120 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KUP93-14A13-120 Payment Methods**



















### **KUP93-14A13-120 Shipping Methods**













If you have any question about KUP93-14A13-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com