

KUSB1052 Information



For Reference Only

Part Number KUSB1052

Manufacturer Volgen America/Kaga Electronics USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 10W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KUSB1052 Specifications

Manufacturer Part Number KUSB1052 Manufacturer Volgen America/Kaga Electronics USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Manufacturer Part Number	KUSB1052
Package - Series - Region Utilized - Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package - Series - Region Utilized - Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized - Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)		AC DC Desktop, Wall Adapters
Region Utilized-FormWall MountInput TypeFixed BladeVoltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)2APower (Watts)10WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature10°C ~ 40°COutput ConnectorUSB A ReceptacleSize / Dimension2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Series	-
Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 240 VAC	Region Utilized	-
Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 100 ~ 240 VAC 10W 10W 10W 10W 10W 10W 10W 10	Form	Wall Mount
Voltage - Output Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 5V 10W 10W 10W 10W 10W 10W 10W 10	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 10W Annual Consumption 10W Annual Commercial 10 C ~ 40°C USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Voltage - Output	5V
No Load Power Consumption 300mW (Max) Polarization -	Current - Output (Max)	2A
Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Power (Watts)	10W
Applications ITE (Commercial) Efficiency Level V Operating Temperature 10°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB A Receptacle Size / Dimension 2.05° L x 1.14° W x 1.81° H (52.0 mm x 28.9 mm x 46.0 mm)	Polarization	-
	Applications	ITE (Commercial)
Output Connector USB A Receptacle Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Efficiency	Level V
Size / Dimension 2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	USB A Receptacle
Report errors?	Size / Dimension	2.05" L x 1.14" W x 1.81" H (52.0mm x 28.9mm x 46.0mm)
		Report errors?

KUSB1052 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KUSB1052 Payment Methods



















KUSB1052 Shipping Methods













If you have any question about KUSB1052, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com