

L12J330

L12J330 Information



Part Number	L12J330	
Manufacturer	Ohmite	
Category	Resistors Chassis Mount Resistors	
Description	RES CHAS MNT 330 OHM 5% 12W	
Package	Radial, Tubular	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L12J330 Specifications

ManufacturerOhmieCategoryResistorsChassis Mount ResistorsPackageRadial, TubularSeries270Resistance330 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating TemperatureFlame Retardant Coating, SafetyCoating, Housing TypeSrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, Tubular		
CategoryResistorsPackageRadial, TubularPackageRadial, TubularSeries270Resistance330 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTomperature Coefficient±260ppm/°COperating TemperatureFlame Retardant Coating, SafetyPotousing TypeVireous Enamel CoatedSize / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Failure RateSolder Lugs	Manufacturer Part Number	L12J330
Chassis Mount ResistorsPackageRadial, TubularSeries270Resistance330 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting Feature0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Failure Rate-	Manufacturer	Ohmite
PackageRadial, TubularSeries270Resistance330 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeSrackets (not included)Nounting Feature0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
Series270Resistance330 OhmsTolerance±5%Power (Wats)12WCompositionWirewoundTemperature Coefficient±260pm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension-Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance330 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting Feature0.313" Dia x 1.748" L (7.94mm x 44.40mm)Size / Dimension.Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension-Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Series	270
Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Resistance	330 Ohms
CompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Tolerance	±5%
Temperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Power (Watts)	12W
Operating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Composition	Wirewound
FeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Temperature Coefficient	±260ppm/°C
Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Operating Temperature	-55°C ~ 350°C
Mounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Features	Flame Retardant Coating, Safety
Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	0.313" Dia x 1.748" L (7.94mm x 44.40mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

L12J330 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about L12J330, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com