

L12J560 Information

M Ca Heisener.com

Part Number L12J560
Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 560 OHM 5% 12W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L12J560 Specifications

Manufacturer Part NumberL12J560ManufacturerOhmiteCategoryResistorsPackageRadial, TubularSeries270Resistance560 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Report errors?		
CategoryResistorsPackageRadial, TubularSeries270Resistance560 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	L12J560
PackageRadial, TubularSeries270Resistance560 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer	Ohmite
PackageRadial, TubularSeries270Resistance560 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
Series270Resistance560 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance560 OhmsTolerance±5%Power (Watts)12WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.313" Dia x 1.748" L (7.94mm x 44.40mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 12W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.313" Dia x 1.748" L (7.94mm x 44.40mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	270
Power (Watts) Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.313" Dia x 1.748" L (7.94mm x 44.40mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Resistance	560 Ohms
Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.313" Dia x 1.748" L (7.94mm x 44.40mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Tolerance	±5%
Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.313" Dia x 1.748" L (7.94mm x 44.40mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	12W
Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.313" Dia x 1.748" L (7.94mm x 44.40mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - - - - - - - - - - - - -	Composition	Wirewound
Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.313" Dia x 1.748" L (7.94mm x 44.40mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±260ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.313" Dia x 1.748" L (7.94mm x 44.40mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Brackets (not included) Size / Dimension 0.313" Dia x 1.748" L (7.94mm x 44.40mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Features	Flame Retardant Coating, Safety
Size / Dimension 0.313" Dia x 1.748" L (7.94mm x 44.40mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	0.313" Dia x 1.748" L (7.94mm x 44.40mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

L12J560 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L12J560 Payment Methods





















L12J560 Shipping Methods













If you have any question about L12J560, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com