



### L15S040.T Information

Heisener.com

For Reference Only

Part Number L15S040.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 40A 150VAC/VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# L15S040.T Specifications

Manufacturer Part NumberL15S040.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)Report errors?		
Category Electrical, Specialty Fuses  Package Cartridge, Non-Standard Series POWR-GARD? L15S Fuse Type Cartridge Current Rating 40A Voltage Rating - AC Voltage Rating - DC 150V Response Time Fast Applications Semiconductors Features - Class - Approvals Ceç CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Cirridge Cartridge, Non-Standard Size / Dimension  Cirridge Cartridge, Non-Standard Size / Dimension  Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	L15S040.T
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating40AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  40A 40A 40A 40A 40A 40A 40A 40A 40A 40	Series	POWR-GARD? L15S
Voltage Rating - AC  Voltage Rating - DC  150V  Response Time Fast  Applications Semiconductors  Features - Class - Approvals CE, CSA, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  150V  15	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Semiconductors  Features - Class - Approvals CE, CSA, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  150V  150V  160V	Current Rating	40A
Response Time Fast Applications Semiconductors  Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Voltage Rating - AC	150V
Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Semiconductors - CE, CSA, UR - CE, C	Voltage Rating - DC	150V
Features - Class - Class - CE, CSA, UR Operating Temperature - Cesting Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Approvals	CE, CSA, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Breaking Capacity @ Rated Voltage	100kA AC, 20kA DC
Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 2.000" L (20.60mm x 50.80mm)
		Report errors?

#### L15S040.T Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# L15S040.T Payment Methods





















### L15S040.T Shipping Methods













If you have any question about L15S040.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com