

L15S045.T

L15S045.T Information



Part Number	L15S045.T	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CARTRIDGE 45A 150VAC/VDC	
Package	Cartridge, Non-Standard	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L15S045.T Specifications

Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? L15S Fuse Type Cartridge Current Rating 45A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature 100KA AC, 20KA DC Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Manufactures Cartridge, Non-Standard		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100kA AC, 20kA DCBreaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Manufacturer Part Number	L15S045.T
Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-Operating TemperatureCE, CSA, UROperating Temperature100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Type100kA AC, 20kA DCBreaking Capacity @ Rated Voltage100kA AC, 20kA DCPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100kA AC, 20kA DCBreaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / Case0.811" Dia x 2.000" L (20.60mm x 50.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating45AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100KA AC, 20kA DCBreaking Capacity @ Rated VoltageHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Package	Cartridge, Non-Standard
Current Rating45AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100kA AC, 20kA DCBreaking Capacity @ Rated VoltageHolderMounting Type6.Package / Case0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Series	POWR-GARD? L15S
Voltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100kA AC, 20kA DCBreaking Capacity @ Rated VoltageHolderMounting TypeKender StandardPackage / Case0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Fuse Type	Cartridge
Voltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Current Rating	45A
Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Voltage Rating - AC	150V
ApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Voltage Rating - DC	150V
InInFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Response Time	Fast
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Applications	Semiconductors
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Class	-
Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Approvals	CE, CSA, UR
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Breaking Capacity @ Rated Voltage	100kA AC, 20kA DC
Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 2.000" L (20.60mm x 50.80mm)
		Report errors?

L15S045.T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about L15S045.T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com