



### L15S050.TX100 Information

Heisener.com

Part NumberL15S050.TX100ManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE FAST SEMICONDUCTOR 50A 150V

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### L15S050.TX100 Specifications

Manufacturer Part NumberL15S050.TX100ManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)		
Category         Circuit Protection           Electrical, Specialty Fuses           Package         Cartridge, Non-Standard           Series         POWR-GARD? L15S           Fuse Type         Cartridge           Current Rating         50A           Voltage Rating - AC         150V           Voltage Rating - DC         150V           Response Time         Fast           Applications         Semiconductors           Features         -           Class         -           Approvals         CSA, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         100kA AC, 20kA DC           Mounting Type         Holder           Package / Case         Cartridge, Non-Standard           Size / Dimension         0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Manufacturer Part Number	L15S050.TX100
Bectrical, Specialty Fuses  Package Cartridge, Non-Standard  Series POWR-GARD? L15S Fuse Type Cartridge Current Rating SoA Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  Cartridge, Non-Standard Size / Dimension	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard  Series POWR-GARD? L15S  Fuse Type Cartridge  Current Rating 50A  Voltage Rating - AC 150V  Voltage Rating - DC 150V  Response Time Fast  Applications Semiconductors  Features - Class - Approvals CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Category	Circuit Protection
Series POWR-GARD? L15S Fuse Type Cartridge Current Rating 50A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Semiconductors Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 50A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Semiconductors Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension  CSA, UR Cartridge, Non-Standard Size / Dimension  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard  Size / Dimension	Package	Cartridge, Non-Standard
Current Rating 50A  Voltage Rating - AC 150V  Voltage Rating - DC 150V  Response Time Fast  Applications Semiconductors  Features - Class - Approvals CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Series	POWR-GARD? L15S
Voltage Rating - AC  Voltage Rating - DC  150V  Response Time  Fast  Applications  Semiconductors  Features  - Class  - Approvals  CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  150V  150	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Semiconductors  Features - Class - Approvals CSA, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  150V Fast CSA Fast Fast Cemiconductors - Cext. Cast.	Current Rating	50A
Response Time Applications Semiconductors  Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Semiconductors - Cemiconductors - Cemiconductors - Communication CSA, UR CSA, UR - CSA, UR	Voltage Rating - AC	150V
Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  Semiconductors  - Semiconductors  Semiconductors  - Semiconductors  Semiconductors  - Semiconductors  Semiconductors  - Cantridage, Value  - Size / Dimension  Semiconductors  - Semiconductors  - Semiconductors  - Cantridage, Value  - Size / Dimension  Semiconductors  - Cantridage, Value  - Size / Dimension  Semiconductors  - Cantridage, Value  Size / Dimension  Semiconductors  Semiconductors  - Cantridage, Value  Size / Dimension	Voltage Rating - DC	150V
Features - Class - CSA, UR  Approvals CSA, UR  Operating Temperature - Freaking Capacity @ Rated Voltage 100kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Response Time	Fast
Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Applications	Semiconductors
Approvals  CSA, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  100kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Approvals	CSA, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Breaking Capacity @ Rated Voltage	100kA AC, 20kA DC
Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 2.000" L (20.60mm x 50.80mm)
		Report errors?

### L15S050.TX100 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# L15S050.TX100 Payment Methods



















### L15S050.TX100 Shipping Methods













If you have any question about L15S050.TX100, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com