



L15S060.T Information

Heisener.com

Part Number L15S060.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 60A 150VAC/VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L15S060.T Specifications

Manufacturer Part NumberL15S060.TManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Manufacturer Part Number	L15S060.T
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? L15S Fuse Type Cartridge Current Rating 60A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating60AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Semiconductors Features - Class - Approvals Ce, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 60A 60A 60A 60A 60A 60A 60A 60A 60A 60	Series	POWR-GARD? L15S
Voltage Rating - AC Voltage Rating - DC 150V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 150V 15	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals Ce, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 150V Fast CE, CSA CE, CSA 150V	Current Rating	60A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Semiconductors - Cemiconductors - CE, CSA, UR - CE, CSA,	Voltage Rating - AC	150V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Semiconductors - CE, CSA, UR - CE, CSA, UR - Holder - Holder Holder Cartridge, Non-Standard 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Voltage Rating - DC	150V
Features - Class - Class - CE, CSA, UR Operating Temperature - Cepacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Approvals	CE, CSA, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Breaking Capacity @ Rated Voltage	100kA AC, 20kA DC
Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 2.000" L (20.60mm x 50.80mm)
•		Report errors?

L15S060.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L15S060.T Payment Methods


































If you have any question about L15S060.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com