

L15S300.T

L15S300.T Information



Part Number	L15S300.T	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CRTRDGE 300A 150VAC/100VDC	
Package	Cylindrical, Blade Terminal (Bolt)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L15S300.T Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L15SFuse TypeCatridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DCFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100K AC, 20kA DCPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC100VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100KA AC, 20kA DCBreaking Capacity @ Rated Voltage100KA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Manufacturer Part Number	L15S300.T
Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC100VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100kA AC, 20kA DCBreaking Capacity @ Rated VoltageDolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC100VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100k AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.00" Dia x 1.157" L (25.40mm x 29.40mm)	Category	Circuit Protection
SeriesPOWR-GARD? L15SFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC100VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100kA AC, 20kA DCBreaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / Case1,000" Dia x 1.157" L (25.40mm x 29.40mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC100VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100KA AC, 20kA DCBreaking Capacity @ Rated VoltageBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating300ACurrent Rating - AC150VVoltage Rating - DC100VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature100kA AC, 20kA DCBreaking Capacity @ Rated VoltageBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Series	POWR-GARD? L15S
Voltage Rating - AC150VVoltage Rating - DC100VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Fuse Type	Cartridge
Voltage Rating - DC100VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Current Rating	300A
Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Voltage Rating - AC	150V
ApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Voltage Rating - DC	100V
InInFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Response Time	Fast
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Applications	Semiconductors
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Class	-
Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Operating Temperature	-
Package / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Breaking Capacity @ Rated Voltage	100kA AC, 20kA DC
Size / Dimension 1.000" Dia x 1.157" L (25.40mm x 29.40mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.000" Dia x 1.157" L (25.40mm x 29.40mm)
		Report errors?

L15S300.T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

L15S300.T Payment Methods

L15S300.T Shipping Methods



If you have any question about L15S300.T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com