



### L175J15K Information

Heisener.com

Part Number L175J15K
Manufacturer Ohmite
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 15K OHM 5% 175W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# L175J15K Specifications

Manufacturer Part NumberL175J15KManufacturerOhmiteCategoryResistorsPackageRadial, TubularSeries270Resistance15 kOhmsTolerance±5%Power (Watts)175WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 8.500" L (28.60mm x 215.90mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Report errors?		
Category  Resistors  Chassis Mount Resistors  Package  Radial, Tubular  Series  270  Resistance  15 kOhms  Tolerance  ±5%  Power (Watts)  175W  Composition  Wirewound  Temperature Coefficient  ±260ppm/°C  Operating Temperature  -55°C ~ 350°C  Features  Flame Retardant Coating, Safety  Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate	Manufacturer Part Number	L175J15K
Chassis Mount Resistors  Package Radial, Tubular  Series 270  Resistance 15 kOhms  Tolerance ±5% Power (Watts) 175W  Composition Wirewound  Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C  Features Flame Retardant Coating, Safety  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular  Failure Rate	Manufacturer	Ohmite
PackageRadial, TubularSeries270Resistance15 kOhmsTolerance±5%Power (Watts)175WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 8.500" L (28.60mm x 215.90mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
Series270Resistance15 kOhmsTolerance±5%Power (Watts)175WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 8.500" L (28.60mm x 215.90mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance 15 kOhms Tolerance ±5% Power (Watts) 175W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 8.500" L (28.60mm x 215.90mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Package	Radial, Tubular
Tolerance ±5%  Power (Watts) 175W  Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features Flame Retardant Coating, Safety  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Series	270
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±260ppm/°C  Operating Temperature  -55°C ~ 350°C  Features  Flame Retardant Coating, Safety  Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Resistance	15 kOhms
Composition  Wirewound  ±260ppm/°C  Operating Temperature  -55°C ~ 350°C  Features  Flame Retardant Coating, Safety  Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max)  -  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Tolerance	±5%
Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features Flame Retardant Coating, Safety  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Power (Watts)	175W
Operating Temperature  -55°C ~ 350°C  Features  Flame Retardant Coating, Safety  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -  -55°C ~ 350°C  Flame Retardant Coating, Safety  Vitreous Enamel Coated  Soated  Solder Lugs  Radial, Tubular  -	Composition	Wirewound
Features Flame Retardant Coating, Safety  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max) - Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Temperature Coefficient	±260ppm/°C
Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max)  - Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Operating Temperature	-55°C ~ 350°C
Mounting Feature  Brackets (not included)  Size / Dimension  1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  Brackets (not included)  Size / Dia x 8.500" L (28.60mm x 215.90mm)  - Lead Style  Solder Lugs  Radial, Tubular	Features	Flame Retardant Coating, Safety
Size / Dimension 1.126" Dia x 8.500" L (28.60mm x 215.90mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.126" Dia x 8.500" L (28.60mm x 215.90mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

### L175J15K Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## L175J15K Payment Methods





















## L175J15K Shipping Methods













If you have any question about L175J15K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com